Supply and Delivery of SEWAGE VACUUM TRUCK (12,000 liters) to Marib governorate RFQ#4200282927				
Technical Specifications			Quantity	Unit PRICE (USD)
	Condition	Brand new		
General	Production Year	Not less than 2020		
	Loading capacity	12m3		
	Overall Dimension	7855×2490×3425 mm		
	GVW / Kerb Weight	8950 kg / 18000kg		
Сар	Cab Capacity	3 seats		
Engine	Air Conditioner	Heating/cooling air conditioner		
	Fuel Type	Diesel		
	Cooling type	water cooled		
	Engine size	6 cylinders, turbo		
	Torque	above 720 NM.		
	Power	240HP (177Kw)		
	Displacement	7790ml		
	Emission Standard	Euro-5		
Chassis	Drive Type	4X2 (left hand drive)		
	Transmission	6-shift speed levers with 1 reverse		
	Wheelbase/No. of axle	4500 mm / 2 Axle		
	Tire Specification	11.00R20 16PR		
	Tire Number	6 tires and 1 spare tire		
	Max Speed	90 km/h		
	Paint	Metallic paint		
Superstructure	Body capacity	12,000 liters		
	Tanker Material	Carbon Steel		
	Suction Head pipeline	10 m		
	Vacuum Pump brand	Italy Jurop (PN155R)		
	Vacuum Pump advantage	Highly efficient, vacuum rate 93%,	1	
	vacuum Fump auvantage	Quick suction and discharge, suction depth 8m		
	Hose	High quality, wire strengthened hose		
	Control panel	English		
	All standard accessories: Inlet pipe	line, discharge nozzle, basic tool kit, English manual		
Vacuum System	Suction speed	Fill up in 10 minutes		
		Finished in a single 8 minutes		
	Vertical depth of suction	Up to 8 meters		
		Manual + pneumatic + hydraulic		
	Operating position	Car side	-	
		Carbon steel Q355B		
	Tank thickness	6 mm tank, 8 mm head, 4 mm partition		
		Italy Jurop PN155R @19 kw (910m3/h)		
	Leak-proof treatment	Rubber strip + hydraulic lock		
	· ·	The tailgate is fully open, the tail is fully open		
	Blowdown method	Hydraulic lift dumping + air/vacuum blowdown		
		Sight liquid window, hydraulic gauge, 10-meter suction		
		pipe, tail gravity valve, anti-overflow valve, negative pressure meter.		
	Optional configuration	Liquid full alarm self-stop,sliding vane vacuum pump, anti- corrosion treatment in the tank, solid-liquid separation		
Other REQUIREMENTs	Manufacturer Warranty:	filter cartridge + hydraulic auger, cleaning water pump Warranty against manufacturing defects for at least two years (Warranty certificate).		
	Customs	customs clearance is the repsonsibility of the supplier.		
	Delivery location	The Hygiene Improvement Fund office-Marib city		
	After Delivery			
	After Delivery	Printing IOM & KSR Logos using automotive paint		

Supplier signature and stamp :