

## REQUEST FOR QUOTATION (RFQ)

RFQ Reference: [4200473154](#)

Date: 29 May 2023

### **SECTION 1: REQUEST FOR QUOTATION (RFQ) for the provision of [NMCP rehabilitation of TRO warehouses](#)**

International Organisation for Migration (IOM) kindly requests your quotation for the provision of goods, works and/or services as detailed in Annex 1 of this RFQ.

This Request for Quotation comprises the following documents:

Section 1: This request letter

Section 2: RFQ Instructions and Data

Annex 1: Schedule of Requirements

Annex 2: Quotation Submission Form

Annex 3: Technical and Financial Offer

When preparing your quotation, please be guided by the RFQ Instructions and Data. Please note that quotations must be submitted using **Annex 2: Quotation Submission Form and Annex 3 Technical and Financial Offer**, by the method and by the date and time indicated. It is your responsibility to ensure that your quotation is submitted on or before the deadline. Quotations received after the submission deadline, for whatever reason, will not be considered for evaluation.

All vendors should confirm registration on the IOM YEMEN [Vendor Registration Platform](#).

Thank you and we look forward to receiving your quotations.

Approved by:

Signature: \_\_\_\_\_

Name: Click or tap here to enter text.

Title: Click or tap here to enter text.

Date: Click or tap here to enter text.

## SECTION 2: RFQ INSTRUCTIONS AND DATA

<b>Deadline for the Submission of Quotation</b>	11 June 2023 If any doubt exists as to the time zone in which the quotation should be submitted, refer to <a href="http://www.timeanddate.com/worldclock/">http://www.timeanddate.com/worldclock/</a> .
<b>Method of Submission</b>	<p>Quotations must be submitted as follows:</p> <p><input checked="" type="checkbox"/> E-tendering (IOM Yemen Tender <a href="mailto:iomyementender@iom.int">iomyementender@iom.int</a> )</p> <p><input type="checkbox"/> Email</p> <p><input type="checkbox"/> Courier / Hand delivery</p> <p><input type="checkbox"/> Other Click or tap here to enter text.</p> <p>Bid submission address: <a href="mailto:iomyementender@iom.int">iomyementender@iom.int</a></p> <ul style="list-style-type: none"> <li>▪ File Format: PDF</li> <li>▪ File names must be maximum 60 characters long and must not contain any letter or special character other than from Latin alphabet/keyboard.</li> <li>▪ All files must be free of viruses and not corrupted.</li> <li>▪ Max. File Size per transmission: Click or tap here to enter text.</li> <li>▪ Mandatory subject of email: <a href="#">4200473154- NMCP rehabilitation of TRO warehouses</a></li> <li>▪ Multiple emails must be clearly identified by indicating in the subject line "email no. X of Y", and the final "email no. Y of Y."</li> <li>▪ It is recommended that the entire Quotation be consolidated into as few attachments as possible.</li> <li>▪ The proposer should receive an email acknowledging email receipt.</li> </ul>
<b>Cost of preparation of quotation</b>	IOM shall not be responsible for any costs associated with a Supplier's preparation and submission of a quotation, regardless of the outcome or the manner of conducting the selection process.
<b>Supplier Code of Conduct</b>	All prospective suppliers must read the UN Supplier Code of Conduct and acknowledge that it provides the minimum standards expected of suppliers to the UN. The Code of Conduct, which includes principles on labour, human rights, environment and ethical conduct may be found at: <a href="http://ungm.org">Supplier Code of Conduct (ungm.org)</a> .
<b>Conflict of Interest</b>	UN encourages every prospective Supplier to avoid and prevent conflicts of interest, by disclosing to UN if you, or any of your affiliates or personnel, were involved in the preparation of the requirements, design, specifications, cost estimates, and other information used in this RFQ.
<b>General Conditions of Contract</b>	Any Purchase Order or contract that will be issued as a result of this RFQ shall be subject to the IOM General Conditions of Contract for provision of goods/services/transportation/medical services available at <a href="https://www.iom.int/do-business-us-procurement">https://www.iom.int/do-business-us-procurement</a> .
<b>Eligibility</b>	Bidders shall have the legal capacity to enter into a binding contract with IOM and to deliver in the country, or through an authorized representative.
<b>Currency of Quotation</b>	Quotations shall be quoted in USD
<b>Duties and taxes</b>	<p>The International Organization for Migration is exempt from all direct taxes, except charges for public utility services, and is exempt from customs restrictions, duties, and charges of a similar nature in respect of articles imported or exported for its official use. All quotations shall be submitted net of any direct taxes and any other taxes and duties, unless otherwise specified below:</p> <p>All prices shall:</p> <p><input checked="" type="checkbox"/> be inclusive of VAT and other applicable indirect taxes</p> <p><input type="checkbox"/> be exclusive of VAT and other applicable indirect taxes</p>

<b>Language of quotation and documentation including catalogues, instructions and operating manuals</b>	English
<b>Documents to be submitted</b>	Bidders shall include the following documents in their quotation: <input checked="" type="checkbox"/> Annex 2: Quotation Submission Form duly completed and signed <input checked="" type="checkbox"/> Annex 3: Technical and Financial Offer duly completed and signed and in accordance with the Schedule of Requirements in Annex 1 <input checked="" type="checkbox"/> Past Experience with IOM/UN/INGOs in Similar Construction Materials supply
<b>Quotation validity period</b>	Quotations shall remain valid for 60 days from the deadline for the Submission of Quotation.
<b>Price variation</b>	No price variation due to escalation, inflation, fluctuation in exchange rates, or any other market factors shall be accepted at any time during the validity of the quotation after the quotation has been received.
<b>Partial Quotes</b>	<input checked="" type="checkbox"/> Not permitted <input type="checkbox"/> Permitted
<b>Payment Terms</b>	<input checked="" type="checkbox"/> IOM will pay the Contractor 1st instalment “90 % within 30 days “only on confirmation by IOM of satisfactory progress toward the completion of work as per Bill of Quantities <input checked="" type="checkbox"/> retention (10 % of the total PO price) will be held for a year .The amount shall be released to the Contractor after the Organization issues to the Contractor, the Certificate of Final Acceptance for the works
<b>Contact Person for correspondence, notifications and clarifications</b>	Focal Per son: <b>Majeda Al-Hamidi</b> E-mail address: <b>malhamidi@iom.int</b> <b>Attention: Quotations shall not be submitted to this address but to the address for quotation submission above.</b>
<b>Clarifications</b>	Requests for clarification from bidders will not be accepted any later than 2days before the submission deadline. Responses to request for clarification will be communicated <b>Majeda Al-Hamidi via email address (malhamidi@iom.int)</b> Click or tap to enter a date.
<b>Evaluation method</b>	<input checked="" type="checkbox"/> The contract will be awarded to the lowest price substantially compliant offer. <input checked="" type="checkbox"/> matching the Evaluation Criteria
<b>Evaluation criteria</b>	<input checked="" type="checkbox"/> Full compliance with all requirements as specified in Annex 1 <input checked="" type="checkbox"/> Full acceptance of the General Conditions of Contract <input type="checkbox"/> Comprehensiveness of after-sales services <input checked="" type="checkbox"/> Earliest Delivery /shortest lead time <input checked="" type="checkbox"/> Past experience with IOM/UN/INGOs in similar/Original catalogues /list of offered materials with actual specification, brand name.
<b>Right not to accept any quotation</b>	IOM is not bound to accept any quotation, nor award a contract or Purchase Order
<b>Right to vary requirement at time of award</b>	At the time of award of Contract or Purchase Order, IOM reserves the right to vary (increase or decrease) the quantity of services and/or goods, by up to a maximum 25% of the total offer, without any change in the unit price or other terms and conditions.
<b>Type of Contract to be awarded</b>	CONSTRUCTION AGREEMENT
<b>Expected date for contract award.</b>	
<b>Policies and procedures</b>	This RFQ is conducted in accordance with Policies and Procedures of IOM

<b>UNGM registration</b>	IOM is encouraging all suppliers to register at the United Nations Global Marketplace (UNGM) website at <a href="http://www.ungm.org">www.ungm.org</a> . The Bidder may still submit a quotation even if not registered with the UNGM, however, if the Bidder is selected for Contract award of USD 100,000 and above, the Bidder is recommended to register on the UNGM prior to contract signature. For vendors who do not have the technical means to register in UNGM, the UNGM has implemented an assisted vendor registration functionality that allows IOM procurement personnel to add local vendors to the UNGM.
--------------------------	---

## ANNEX 1: SCHEDULE OF REQUIREMENTS

BoQ Link :

[BOQs-NMCP rehabilitation of TRO warehouses .xlsx](#)

### Technical Specifications for Goods:

Item No	Minimum technical requirements	Unit	Quantity
1	Vertical cooling refrigerator/ It operates with electric, equipped with a modern and safe system, a world-famous brand with an authorized agent in Yemen. The need to provide a guarantee of maintenance and provision of spare parts for all services and after-sales, with a guarantee of damage and repair of any defects or manufacturing defects that appear after the supply period of no less than twelve months from the date of supply/ Not less 12 /ft / Fixed milky white (unit-cooling refrigerator)	EA	1
2	: Supply and installation of curtains for the windows of the following: 1. The medicine and insecticides warehouses 2. Training hall (lectures) 3. Training hall (laboratory) 4. The parasitological examination laboratory. 5. Entomological training hall / Made of velvet and sterilized cloth of reinforced type /Height: 300 cm, width 300 cm /Dark green and opaque color is preferred for all curtains required for the aforementioned premises (unit -A piece divided into two equal parts for each window with all its accessories, according to the shown dimensions )	EA	4
3	Supplying and installing curtains for the windows on the remaining premises in the building/ piece divided into two equal parts for each window with all its accessories, according to the shown dimensions/Made of dry and heavy cloth in the form of a whole piece, excellent quality/ Height: 300 cm + width 300 cm / Beige color is preferred (unit-A piece divided into two equal parts for each window with all its accessories, according to the shown dimensions )	EA	12
4	Supply and installation of curtains for the windows of the following: 1. The medicine and insecticides warehouses 2. Training hall (lectures) 3. Training hall (laboratory) 4. The parasitological examination laboratory. 5. Entomological training hall / Made of velvet and sterilized cloth of reinforced type /Height: 300 cm, width 425 cm /Dark green and opaque color is preferred for all curtains required for the aforementioned premises (unit -A piece divided into two equal parts for each window with all its accessories, according to the shown dimensions )	EA	3
5	Required accessories for laboratory tables: Supply and assembly of cupboards (reserve tanks made of aluminum and fiberglass. Configuration and design of one cupboard is as shown in the attached form in the shape of a rectangle. It is required to assemble the cupboards firmly to maintain the premises of the laboratories mentioned above and at an appropriate height above Laboratory tables directly, and at the rate of one cupboard for each laboratory/ Made of aluminum and fiberglass that conforms to the same type and specifications of which the laboratory tables are made, with the same thickness and according to the design and configuration shown in the attached form. Middle of the cupboard is divided into two parts: an upper and a lower section equal by means of one shelf fixed on the inner cavity and made of fiberglass and	EA	2

	surrounded by an aluminum frame and fixed tightly. It has two doors made of reinforced, thick and shock-resistant glass. The two glass doors are surrounded by an aluminum frame fixed by a rubber material (reinforced and heavy plastic) on all sides. The two glass doors are assembled together in an overlapping manner by means of a pull mechanism (side displacement) that is easy and smooth during opening and closing, and it is provided with an aluminum manual handle that is firmly fixed on the frame surrounded by glass (as shown in the model). On each box there is a door assembled on the frame by means of two hinges (iron), and each door is provided with a closure (key with one turn). The two doors are made of fiberglass and surrounded by an aluminum frame on all sides. The sides, base, roof, and background of the cupboard are made of fiberglass surrounded by an aluminum frame, as shown in the model. - All parts and the structure are connected and interconnected tightly and steadily./Matching with the color required for laboratory tables / (unit-A wall cupboard attached to the laboratory tables)		
6	HD- 4K 65 بوصة / شاشة تلفزيونية 65 بوصة / شاشة تلفزيونية Inch TV مع حامل متحرك / 65 بوصة / HD-4K TV screen /HD-4K TV screen with mobile stand/ 65 Inch /For the training halls (1) and (2)	EA	2
7	Epson كمبيوتر مكتبي مع طابعة / Desktop computer with Epson printer / Computer with printer	EA	6
8	Photocopymachine with its table / تصوير مستندات مع الطاولة	EA	1
9	Lazer طابعة / Lazer printer with scanner مع اسكنار	EA	1
10	An educational blackboard consisting of a writable board A fixed base (stand and backrest) for the board used for writing./ The board with the base: entirely made of thick and light weight reinforced iron and painted with a layer of insulating material, weather resistant and non-absorbent for fats and liquids. 2 Board thickness is not less than 2.5cm 3 The front side of the blackboard is coated with a special material (used for writing on) and the material is characterized by the following: high quality, stable and resistant to weather conditions, clear (free of impurities, with a smooth and soft surface, non-absorbent, and stabilizing the materials and liquids used for writing, so that words can be erased and crossed out with ease and re-write new words clearly Large water and oil pens can be used to write on using colored ones The board is carried on a base and fixed to it by means of a mechanism that allows moving the board up and down as needed, in a tight and high-tech manner. The base is equipped with four legs (bracket) designed in a way to fix the board in any position and help to move it with ease../ The board has a rectangular shape with straight sides. Height: not less than 150 cm and not more than 155 cm The width is not less than 90 cm and not more than 95 cm Height: not less than 180 cm and not more than 190 cm - The width is appropriate to the width of the board / Pure white or bright beige and light so that the colors are stable/ (unit - An educational blackboard )	EA	1
11	ثلاجة لحفظ الماء مزودة بالممرات الباردة / ثلاجة تبريد وتسخين الماء Refrigerator (water dispenser) to save water with cold passages / Refrigerator for cooling and heating water	EA	2
12	Office iron cupboards consisting of one piece, vertical shape, containing four drawers (boxes) of iron (pulling) / Entirely made of reinforced iron and coated with an insulating and fire-resistant material (Heavy gauged) 2. The cupboard	EA	18

	contains four drawers (Spaces) of iron metal that makes up the cupboards. 3. Opening and closing the drawers by means of a mechanism that operates with a pull system (smooth sliding) assembled on each drawer separately and designed for a precise technique that works to open and close the drawers with ease and flexibility. 4. Provide the four drawers with a central and tight locking system (Master key) with manual handles assembled on each drawer of resistant material and designed in a suitable way to help open and close drawers 5. All structures and parts of the cupboards are tightly interconnected by a hinge and screws along the manufacturing line. 6. Designing the four drawers in a unified manner in terms of (dimension + composition, internal and external parts + thickness + opening and closing mechanism system)./ The height of the cupboard is not less than 131 cm and not more than 140 cm, the width of the cupboard is not less than 64 cm and not more than 70 cm, the depth of the cupboard is not less than 75 cm / (unit-Iron office Cupboards /Pulling drawers )		
13	Iron office cupboards - consisting of two floors (assembled on top of each other) The upper floor contains two sliding glass doorsThe lower floor contains two sliding iron doors - Design the wheel according to the attached model / The upper floor: contains two reinforced glass doors to resist fire and shocks. The glass is surrounded by a metal frame, fixed with a plastic material stuffed between the glass and the metal frame on all sides 2 . The lower floor: contains two iron doors 3. The two doors assembled on each floor: Designed with an opening and closing mechanism and a sliding side zipper for each door with ease and tightness. It is equipped with a locking mechanism with a one-turn key for each floor separately. Equipped with manual handles installed appropriately to facilitate the opening and closing process, at the rate of one handle on each floor. 4. Each floor contains two metal (iron) shelves with reinforced handles (joints) to install the shelves at the optional level. 5. All parts of the metal wheel (iron) are of the reinforced and resistant type, and coated with a material that is (Heavy-gauged) resistant to burning and shocks. 6. All wheel structures are tightly interconnected by a hinge and screws (Assembly) along the manufacturing line. 7. Designing the two floors of the cupboard in a unified manner in terms of (dimensions + structure), the outer frame of the sides and the back + the interior design (shelves and cavities) + thickness and type of metal...etc../ Height for two floors: not less than 176 cm and not more than 180 cm 2. Width for two floors: not less than 88 cm and not more than 90 cm 3. Depth for two floors: not less than 41 cm and not more than 43 cm / Light Beige -(unit- 2-sets/ Iron office Cupboard)	EA	6
14	Office iron cupboards Consisting of one piece, of two (iron) doors + four iron shelves/ Entirely made of reinforced iron and coated with an insulating and fire-resistant material ( Heavy gauged). 2. The cupboards contain four shelves made of iron, which make up the cupboard. The shelves are fixed with a special reinforced grip that allows each shelf to be assembled at an optional level. 3. The cupboards contain two-doors of iron metal and fixed on them through metal joints (strong steel) perfectly designed to open and close the two doors easily and tightly. 4. Providing the two doors with a locking mechanism with one-turn key + manual handles on each door designed and assembled in a suitable way to facilitate the opening and closing of the doors 5. All frames and parts of the cabinets are tightly interconnected by means of an assembly and screws along the manufacturing line of the cupboards / Height of the cupboard is not less than 180 cm and not more than 183 cm. Width: not less than 90 cm	EA	18

	and not more than 92 cm, and Depth: not less than 43 cm and not more than 46 cm / Light Beige -(unit - Iron office Cupboards/Shelves )		
15	Shelves Office Cupboard (Wooden) Accessories identical to the laboratory training in terms of manufacturing materials type, thickness in addition to the commercial brand and production sources ) / Cupboard structure with the back, shelves and doors of the bottom section are all made of wood pressed with high quality, and shall be identical to the type from which the laboratory training table was made, and with the same external features and thickness Designing and composition of the cupboard chape / Height of the cupboard shall not be less than 165 cm and not more than 170cm Width of the cupboard shall not be less than 80 cm and not more than 85 cm Depth of the cupboard shall not be less than 40 cm and not more than 45 cm Thickness shall not be less than 2 cm / Identical to the color of the laboratory training table / (unit-Wooden Office Cupboard with Shelves )	EA	2
16	Six drawer wooden desk Assembly: The office is composed of one table in the shape of a rectangle. It contains six side drawers, with an average of three drawers assembled on each side. The drawers assembled on both sides of the office are equal in terms of design, shape, size, number of drawers, appearance...etc. / The surface of the entire desk is made of reinforced wood, a highly compressed type (MDF), with a thickness of not less than 2 cm. The other parts of the office sides including the drawers, are made of rust-resistant steel. The entire outer surface of the office shall be covered with a layer of polished wood with an insulating and stable material (resistant to weather conditions and does not absorb fats and liquids) , and the outer surface shall be soft and smooth, with not less than 1.5 cm thick Drawers assembled on both sides of the desk are three, and equipped with a pull system that works easily and efficiently, with a manual handle made of solid and reinforced material, an perfectly attached to each drawer separately (Master Key), the three side drawers are provided with a central locking system / office dimensions Width: Not less than (160 cm) and not more than (165 cm), Depth: Not less than (71 cm) and not more than (80 cm), Height: Not less than 72 cm and not more than 75 cm Dark wooden color is preferred / The four offices/desks are for the technical and administrative perosns at the TRO -(unit-Six drawer wooden desk)	EA	5
17	Three-drawer desk, wooden Assembly: The office is composed of one table. - The office contains three drawers, assembled on one side (from the right side) and a fourth drawer in the front / The whole surface of the desktop is made of reinforced wood, a highly compressed type (MDF). Other parts of the desk including the sides, are made of painted iron, which is resistant to rust and moisture. The whole outer surface of the desk (from all directions and sides) is covered with a layer of wood polished with an insulating and steady material (resistant to weather conditions and does not allow absorption of fats, liquids...etc) where the outer surface shall be smooth and soft from all directions. Thickness of the desk shall not be less than 1.5 cm. Drawers assembled on the right side of the desk shall be three drawers equipped with a pull system that works easily and efficiently, with manual handles made of solid and reinforced material, and fixed tightly for each drawer separately (Master Key), and equipped with a central locking system. / A1. Office Dimensions: The width is not less than 120 cm and not more than 130 cm The depth is not less than 71 cm and not more than 80 cm The height is not less than 72 cm and not	EA	12



	more than 75 cm/ Dark wooden color is preferred- (unit-Wooden Three Drawers Desk)		
18	<p>L-shaped desk: The desk is composed of two tables overlapped with each other in the shape of "L", including a front table + a side table. Each table contains (one box consisting of three drawers). Edges of the desktop (from all directions and sides) are prominently designed and made of solid and resistant material, with a thickness of not less than (5 cm) / An entire office made of highly compressed wood (reinforced MDF type) The entire outer surface of the office shall be covered with a layer of polished wood with an insulating and stable material (resistant to weather conditions and non-absorbing of fats and liquids, etc.) The outer surface for the dressk shall be soft from all sides and directions. Thickness of the desk shall not be less than (1.5 cm) Side boxes: number of two boxes installed on the sides of the office, and each box must be provided with a central locking system (Master Key). The boxes installed on the tables shall consist of 3 drawers provided with pulling system owrking easily and softly, and each drawer has a manual handle made of solid, strong and firmly fixed material, designed in proportion to the size and capacity of each drawer / Office size and dimensions: Width: not less than (180 cm) and not more than (185 cm) Depth: not less than (71 cm) and not more than (80 cm) Height: not less than (72 cm) and not more than (75 cm) / Dark wooden color (unit- L-Shaped Desk )</p>	EA	3
19	<p>/ Wood library: two glass doors &amp; Book Shelf Design and composition of the library: The inner cavity with the front facade of the library consists of two parts The upper section: with an area of (75%) of the total area of the library and contains (2) horizontal shelves installed on top of each other with an equal distance with glass covering the facade. The lower section: with an area of (20%) of the total area of the library and contains two boxes of equal area and each one contains one horizontal shelf + two wooden doors covering the front of the section / Made of wood that conforms to the quality, specifications and brand of wood from which the L-Shaped desk is made as mentioned in the previous item The glass doors are made of reinforced glass covered with a transparent wax layer, two equal pieces according to the area of the upper section of the library, and each one is equipped with a manual handle (without locks) 3. The wooden doors of the lower section consists of two panels covering the front of the lower section, so that each box has a (door) and is equipped with door locks with a key + a suitable manual handle. 4. The glass doors are fixed through two (metal) hinges for each piece, as well as the wooden door / Dimensions of the complete library: Width = not less than (80 cm) and not more than (100 cm) Depth = not less than (38 cm) and not more than (43 cm) Height = not less than (190 cm) and not more than (200 cm) Thickness = not less than ( 1.5 cm) The internal shelves are according to the dimension of the library without leaving any space between the shelves and the inner cavity from all directions. The thickness is not less than (1.5 cm) and the distance between the shelves is not less than (37 cm) and not more than (40 cm). The color shall be coinciding to the color of the L-shaped desk/office-(unit -Library Bookcase / The L-Shaped office is for the offices of : Operations manager+ Epedimology manager+Finance manager. One for each department</p>	EA	3
20	<p>: Wooden library: two glass doors, Glas Door &amp; Book Shelf Design and composition of the library: The inner cavity with the front facade of the library consists of two parts The upper section: with an area of (75%) of the total area of the library and contains (2) horizontal shelves installed on top of each other</p>	EA	2

	<p>with an equal distance + between glass covering the front facade of the section. The lower section: with an area of (20%) of the total area of the library and contains two places of equal area and each place contains one horizontal shelf + two wooden doors covering the front facade of the section / Strengthened and compressed with a high degree (MDF) made of wood, 1. and covered with a layer of polished wood with an insulating material and resistant to:(moisture, light, weather conditions, non-absorption of fats and liquids .... etc.) so that its surface shall be smooth Glass doors: made of reinforced glass,covered with a transparent wax layer, two equal peices, according to the area of the upper section of the library (without shutters), and each peice is equipped with a manual handle Wooden Doors for the lower section shall consist of two pieces that cover the front facade where each piece will have a door , and equipped with key door shutters+a suitable manual handle for each piece, The glass doors shall be fixed through two hinges (metal) for each piece, as well as the wooden doors / Dimensions of the complete library: Width: not less than (80 cm) and not more than (100 cm) Depth = not less than (38 cm) and not more than (43 cm) Height = not less than (190 cm) and not more than (200 cm), Thickness = not less than (1.5 cm) The internal shelves: according to the dimensions of the library without leaving any space between the shelves and the internal cavity from all directions. Thickness = not less than (1.5 cm) = the distance between the shelves shall not be less than (37 cm) and not more than (40 cm) Glass doors thickness = not less than (50 ml) Wood: not less than (3 cm) / Dark wooden color is preferred, so that its color will be stable (unit-Library Bookcase</p>		
21	Supply and installation of fire extinguishers in the warehouses and the building (unit- air extinguisher )	EA	30
22	Providing and installing surveillance cameras/ Surveillance cameras with system and device, day and night, external and internal modern specifications in the warehouses and regional Tehama building / (unit-Surveillance Cameras System)	EA	150
23	Sitting/laboratory chairs Single The seat is rotatable with a low back and two side armrests. The chair is equipped with a high pivot, with a base that can move in all direction /Chair height shall not be not less than (124 cm) and not more than (126 cm), and the width: not less than (70 cm) and not more than (65 cm), and the depth (chair capacity): not less than (55 cm) and not more than (60 cm)/ Chair height shall not be not less than (124 cm) and not more than (126 cm), and the width: not less than (70 cm) and not more than (65 cm), and the depth (chair capacity): not less than (55 cm) and not more than (60 cm)/ Dark and solid blue color is preferred/ (unit -Swivel lab chair)	EA	10
24	Seating chairs: Reception in front of the offices Single / high back Equipped with two backrests, the back with the seat upholstered in artificial leather or reinforced fabric, with fixed metal base / Back seat: upholstered with the artificial leather material or reinforced fabric, high quality , and resistant to the weather conditions and absorption of the fats and liquids. Thickness : not less than 5 cm The armrests and the seats are connected to one another tightly from the two sides. Base: fixed and suitable for size and capacity of the chair The entire design of the chair shall be in a healthy way, comfortable and connected tightly. / Chair height: not less than 94 cm and not more than 96 cm, the width of the chair not less than 50 cm and not more than 53 cm Chair depth: not less than 43 cm / Light, fixed black color is preferred to the leather and fabric -(unit-Single-reception chair )	EA	2

25	Supply of group waiting chairs/ It shall be upholstered in excellent fabric, and equipped with two armrests, and at the end of each chair there shall be a fixed iron base / Average size for three persons, and according to the attached form - Gray color is preferred (unit- Waiting chair )	EA	20
26	Sitting chairs: office – fixed , Single Low-Back Equipped with two armrests on both sides. The back and the seat are upholstered in fabric. Base: Fixed metal (non-movable)./ 1. The back with the seat: made of reinforced and heavy plastic material and upholstered with tightly woven, high-quality fabric of high thickness2.j. Armrests: covered with galvanized and heavy plastic. 3-Chrome Frame: frame of the chair with the base is made of plated tubular steel floor studs. 4. Base of the chair: fixed and linked to the armrests and the chair frame 5. The entire chair is designed in a healthy and comfortable way, and the parts are tightly linked / The height of the chair is not less than 85 cm and not more than 90 cm, the width of the chair is not less than 45 cm and not more than 50 cm, the depth of the chair or capacity: not less than 43 cm /Fixed dark brown color is preferred -(unit- Fixed Chair )	EA	25
27	Sitting chairs for the laboratory training Singly/ low back Equipped with armrests The seat is rotatable in all directions by means of small wheels assembled on arms of the base./ The back and the seat are made of reinforced plastic and upholstered with a tightly woven cloth fabric of high quality and durability that bears the highest degree of pressure and has a thickness of not less than 6 cm. The armrests are made of thick and reinforced plastic. The chair is equipped with a symmetrical (medium) pivot that enables feet of the chair to rest firmly on the ground. The seats are equipped with a mechanism that makes the chair swivel in all directions. The chair is equipped with a base that can be moved in all directions by means of five small wheels on five metal bases in the form of stars. All parts and structure of the chair are designed in a healthy, comfortable and tightly linked manner. / Chair height shall not be less than 92 cm and not more than 95 cm Width not less than 61 cm and not more than 65 cm Depth (chair capacity) not less than 60 cm and not more than 65 cm/ The fixed light blue color is preferred /(unit-Chairs for the laboratory training)	EA	10
28	Sitting chair -lectures , Individual Equipped with one armrest and a writing board (movable) - backrest low size - The back with the seat is upholstered with fabric. - The structure of the chair with the base is made of chrome or reinforced iron. The base shall be stable./ The back with the seat: made of reinforced plastic to resist pressure and upholstered with a high-quality, thick-woven fabric. Thickness of the back together with the seat is not less than 5 cm. 2. The chair frame with the armrest and the base are made of chrome and coated with a stable and insulating material. 3. The chair contains one armrest assembled on the right side (movable), and the armrest contains a wood panel for writing. 4. The entire chair is designed in a healthy and comfortable way, with the knee inclination mechanism, and the structure and parts of the chair are tightly interconnected, as shown in the attached form../ Chair height: not less than 77 cm and not more than 80 cm 2. Chair width not less than 56 cm and not more than 59 cm 3. Chair depth or capacity not less than 54 cm and not more than 57 cm / Fixed Dark Blue /(unit-Lectures Chairs / Fixed )	EA	23
29	Sitting Chairs - swivel - office Single, swivel (moving) Back – Medium Equipped with two armrests The back and the seat are upholstered with synthetic leather The base is a metal movable in all directions / The back with the seat: upholstered with a material (high-quality reinforced synthetic leather, 6cm, with	EA	10

	<p>a thickness of not less than 2 cm). The arm-seats are made of high quality (Polyurethane). Base: Reinforced metal and high quality, movable by 5 small wheels in the form of five stars to facilitate movement without swiveling the chair in all directions. The chair shall be raisable and lowered by a hydraulic system. It shall be also rotatable in all directions, and equipped with a knee inclination mechanism. The entire chair design shall be healthy and comfortable, and the parts are tightly interconnected. / The height of the chair is not less than 100 cm and not more than 120 cm, the width is not less than 50 cm and not more than 55 cm, and the depth or capacity: not less than 52 cm Fixed dark brown color is preferred / (unit-Swivel Chair )</p>		
30	<p>Office waiting set The set consists of four pieces, including one piece with a capacity of three persons , one piece with a capacity of two persons, and two pieces with a capacity of one person - All the pieces that make up the set have a unified design and are equipped with two armrests on the sides for each piece - The backrest and the seat are upholstered in artificial leather and reinforced with each piece - The base is fixed and made of reinforced chrome or stainless steel for each piece separately / The backrest for each piece is high and appropriate to the seat capacity, upholstered with reinforced artificial leather of high quality and thick material that bears the highest degree of pressure on it. Thickness of the back together with the seat is not less than 15 cm - Armrest: Each piece is equipped with two armrests, fixed on the end of each piece, and upholstered with the same material as the back upholstery. -Base: for each piece made of chrome or reinforced steel, with a thickness of not less than 11 cm The design of each piece shall be in a healthy and comfortable way, and the parts are tightly linked/ The large piece for 3 persons: the length is not less than 170 cm and not more than 180 cm, and the width is not less than 75 cm and not more than 78 cm, and the height is not less than 83 cm and not more than 85 cm The medium piece for 2 persons: the length is not less than 112 cm and not more than 114 cm. Depth: not less than 75 cm and not more than 78 cm, Height: not less than 83 cm and not more than 78 cm Individual piece: The width is not less than 74 cm Depth: not less than 75 cm Height not less than 83 cm Depth: not less than 75 cm Height not less than 83 cm / fixed black color is preferred to the fabric -(unit-office waiting set (Sofa) )</p>	EA	10
31	<p>Coffee table set , ade of: reinforced wood A set consists of three pieces One large rectangular table consisting of two floors. One table of small size with a square shape, consisting of two floors / All tables are made entirely of highly compressed wood. The outer surface of the tables is covered with a high layer of MDF, insulating and resistant to weather conditions, and absorbent for fats and liquids, so that the outer surface of the tables (from all directions and sides) shall be soft and smooth. Thickness: for all tables is one and not less than 1.5 cm. Tables are designed appropriately to be used for the administrative business office for the purpose of tea and office hospitality, with fixed and supported bases / The large table: the length is not less than 120 cm and not more than 125 cm, the width (depth) is not less than 75 cm and not more than 65 cm, the height: not less than 45 cm and not more than 47 cm Middle table: width (depth) not less than 60 cm and not more than 65 cm, height: not less than 45 cm / The small table: the width (depth) is not less than 30 cm and not more than 35 cm/ Dark wooden color is preferred -(unit-Coffe/Tea table set consists of 3 pieces )</p>	EA	1

32	<p>Front lecture tables Rectangular shape Fixed base Tables designing are as shown in the attached form/ The table surface is made of high-grade pressed wood covered with an insulation layer of high quality and durability (MDF) that is resistant to weather conditions and does not absorb fats and liquids, and the surface shall be smooth and soft. 2 The table structure is equipped with four fixed legs (base). 3 The frame and legs are completely made of pure chrome and covered with a glossy smooth layer, resistant to weather conditions and non-absorbent for fats and liquids. 4 Thickness of the table is not less than 2 cm 5 Designing all parts of the table are in a cohesive and tight style, in the form of a rectangle, and the sides of the surface are a straight line, according to the attached model./ 1. Height of the table is not less than 72 cm and not more than 75 cm2. Length of the table is not less than 160 cm and not more than 165 cm. 3.Width (depth) of the table is not less than 75 cm/ Surface color: Fixed dark wooden color Frame with the legs: fixed and shining chrome color /(unit-Front lecture tables )</p>	EA	2
33	<p>Supply and assembly of two laboratory tables (laboratory bench) in the shape of the letter "U" made of aluminum. One table consists of three sections (two side and opposite sections + a third section connected between them at the of each section). Design and composition of tables: shown in the attached form, and required to be assembled firmly in the premises of the laboratories mentioned above, at the rate of one table for each laboratory with all its required configurations and accessories./ The three sections that make up one table: made of aluminum and reinforced fiberglass. The type is of high quality and durability, and coated with an insulating material that is resistant to fire, weather conditions, acids, laboratory solutions, fats, and liquids, and its thickness shall not be less than The three sections are connected and interconnected tightly. The two side sections of each table are equal in terms of length and configuration, and each section contains the following: A box assembled at the front of each section with one door made of fire-resistant fiberglass and surrounded by an aluminum frame, fixed by two metal hinges and equipped with a key lock. A sliding or aluminum drawer assembled directly above the box (aluminum) and equipped with a manual handle The remaining space of the two side sections with the area of the third section (all hollow) equipped with 4cm aluminum support sufficient to support the table stably while working on it and has a diameter. It is assembled on the edges of each section extending from the highest point of elevation to the ground - It is equipped with a piece of heavy and reinforced plastic in contact with the ground The top surface for each table is completely covered (for three sections) with a layer of cohesive granite and marble, and it is a type that is resistant to acids, laboratory solutions, fats and liquids, and is resistant to weather conditions, with a thickness of not less than The supporting wall of the upper surface of the tables (in laboratory premises) is completely covered along the upper surface of each table with a layer of granite or marble with a height of not less than 10 cm, so that the layer is firmly attached to the wall and adhered tightly to the covering layer of the table surface, and from all sides the covering layer of the table surface and the supporting wall shall be equal in terms of length, type, color, thickness, features...etc/ The length of the two side sections in each table (equal, and the length of one section is not less than 283 cm and not more than 285 cm – The length of the third section in each length (cut off according to the area and dimensions of the laboratory area for each one separately. The required width (depth) for the three sections in each table is not less than 70 cm and not more than 72 cm, and it is equal to three sections in</p>	EA	2

	each table. The required height for the three sections in each table shall be equal to the three sections where it shall not be less than 90cm and not more than 92cm The box dimensions assembled on the side of each section shall be as follow: The width is not less than 53 cm, the depth is not less than 50 cm The sliding drawer height is not less than 70 cm, the width is not less than 40 cm, and the depth is not less than 47 cm./ The dark milky color is preferred for the structure of the table and the marble or granite layer. The light and transparent milky color is preferred./(unit- Laboratory Table )		
34	Laboratory training table, made of wood Consisting of two pieces in the shape of rectangle. Fixed base / The table consists of two pieces, and entirely made of wood pressed with high quality and coated with high quality an insulating layer which is resisting to weather conditions and non-absorption of fats and liquids.....etc The two pieces that consists of the the table Designing, making and thickness is unified for the two pieces Dimensions: Width (Depth)+ Height are unified for the two pieces As for the length: it shall be unified or different in close dimensions, where total length of the two pieces shall be equal with the required length of the table The prominent edges for the two pieces are supported with a solid and thick material Designing the two pieces that consist the table is in the shape of rectangle with fixed base Composition and assemble of the two pieces are in accordance to the attached model, where all parts shall be tightly connected through spiral screws along the manufacturing line ( The required sample for the assembly of the table is shown on the back of the paper/ The total length for the table shall not be less than 440 cm and not more than 450cm Width (depth) of the table shall not be less than 113cm and not more than 120cm Height of the table shall not be less than 70cm and not more than 75cm Thickness shall not be less than 2.5cm / Gray color is preferred /(unit-Wooden Laboratory Training Table )	EA	1
35	Installing a central air extractor for the insecticides and sprayers warehouse /A central air suction system for the insecticides warehouse with an automatic electric separator. The suction works when the warehouse door is opened and then turns off when the door is closed. It can also be controlled manually via the power socket/(unit-Air Extractor (Vaccum Cleaner)	EA	2
36	General building maintenance - بالعدد مفاقد الشبائيك (نوافذ) والابواب الحديدية نوع (لوفر) ويشمل العمل الصنفرة وثلاثة اوجهة بريمر مانع للصداء وثلاث اوجهة دهان خاص بالحديد والتثبيت والتلحيم ويشمل المفصلات والمغالق وكل ما يلزم وبحسب تعليمات المهندس المشرف In number: Checking windows and iron doors, (Louvre) type. The includes sanding, three sides of an anti-rust primer, and three sides of paint for iron, with fixing and welding, including hinges, bolts and all necessary things, according to the instructions of the supervising engineer -(unit-number of windows)	EA	7
37	General building maintenance - بالمتر المربع دهان زيتي نصف لمعه للقواطع الداخليه - والجدران والاعمدة بدهان زيتي نصف لمعه (شلد) نوعية معتمده من قبل المهندس ثلاثة اوجه مع المعجنه والصنفرة وطبقة الأساس للحصول على سطح مستوي وناعم وباللون المحدد حسب تعليمات المهندس المشرف والتمن يشمل جميع مستلزمات الاعمال In square meter: Semi-glossy oil paint for interior partitions, walls and columns with semi-glossy oil paint (Shield), quality approved by the engineer, three sides with putty, sanding and base coat to obtain a flat and smooth surface and with the specified color according to the instructions of the supervising engineer. The price shall include all works requirements-(unit- 2م Square Meter )	meter	2,400



38	<p>اعمال الدهانات : بالمتر المربع : دهان املشن (شيلد) للسقف والجسور وبطن السلالم الثلاثة اوجهة لون ابيض للحدود على سطح مستوي وناعم مع استخدام المعجنه والتمن يشمل جميع مستلزمات الاعمال بحسب المواصفات وتعليمات المهندس المشرف</p> <p>Painting Works In square meters: Emulsion paint (shield) for the ceiling, bridges, and belly of the three staircases, white color faces, to obtain a flat and smooth surface, with the use of paste. The price shall include all work requirements according to the specifications and instructions of the supervising engineer -(unit-2م Square Meter</p>	meter	580
39	<p>General building maintenance - بالعدد مفاقةة غرف التفتيش وتشمل التجفيف والتنظيف وتكسير التلايبس المتهاك مع بناء بك صم (40*20*20) لغرف التفتيش المتهاة نفس المواصفات القديمة ثم التلبس جيدا باسمنت مقاوم للاملاح مع مراعاة الميول مع اصلاح اغطية غرف التفتيش وتغيير اغطية جديدة للاماكن التالفة وان يكون التلايبس داخليا وخارجيا لجميع غرف التفتيش حسب تعليمات المهندس المشرف</p> <p>In number, inspecting manholes including drying, cleaning and cracking of dilapidated panels, with the construction of solid blocks (40 * 20 * 20) for dilapidated manholes, with same old specifications. Then, plastering well using salt-resistant cement, taking into account inclinations, repairing manhole covers, changing new covers for the damaged places. The plastering for all manholes shall be internally and externally, as per the instructions of the supervising engineer (Unit- number manholes)</p>	EA	17
40	<p>General building maintenance - اعمال البردورات بالمتر الطولي توريد وتركيب بردورات خرسانية خاصة بالطرق ( 60*35*15) سم مصنعة البيا والبناء ميسم 6مم والتمن يشمل الحفر والاساس بالإضافة الى وسادة خلفية من الخرسانة العادية وجميع المستلزمات والدهان باللونين الأصفر والأسود دهان بلاستيكي مقاوم للظروف الجوية والرطوبة حسب تعليمات المهندس المشرف</p> <p>Curbstones Works In linear meter: Supplying and installing concrete curbs for roads (60* 35*15)cm, automatically manufactured, and the construction is 6 mm thick. The price shall include excavation and foundation, in addition to a back pad of regular concrete. All supplies and paints shall be in yellow and black colors, and shall be plastic paint that is resistant to weather conditions and moisture, and as per the instructions of the supervising engineer-Unit-م/ط Linear/meter</p>	EA	40
41	<p>General building maintenance - بالمتر المربع تسوية الموقع مع رفع المخلفات وإزالة جميع الأشجار والمواد المكومة في الموقع ونقل المخلفات الى المكان المحدد لها. وعمل زراعة بالعشب</p> <p>In square meter, the site shall be levelled, along with removing the debris and all trees and materials piled up on the site. The debris shall be transported to the designated place. In addition, grass and ornamental plants shall be planted in the dirt spaces besides providing a drip irrigation system -(unit-2م Square Meter )</p>	EA	500
42	<p>General building maintenance - بالمتر المربع توريد وتركيب شبك حديد للسور حسب المواصفات السابقة وبحسب تعليمات المهندس المشرف</p> <p>In square meter: supplying and installing iron mesh for the fence according to the previous specifications and instructions of the supervising engineer (unit-2م Square Meter )</p>	meter	210
43	<p>General building maintenance - بالعدد توريد وتركيب أبواب المونيوم بقطاع لا يقل عن (10سم) إيطالي وعمل الواح كبس (ميلامي) مغطاء بشرائح المونيوم المسقول درجة أولى وبعد اعتماد القطاعات للحلوق والمقابض والاطارات المطاطية ( للحمامات والمكاتب) بنفس النوعية السابقة والتمن يشمل جميع المستلزمات من المقابض والبراويز والمغالق والبيدات من نوع (بالي ايطالي) والمفصلات واعمال التثبيت وذراع الاغلاق التلقائي (هيدروليكي) ومصدات ارضية للابواب على ان تكون</p> <p>In number: Supplying and installing aluminum doors with a sector of not less than (10 cm), Italian, and making press plates (Melami) covered with first-class polished aluminum slices,</p>	EA	11

	and this is after approving the sectors for rings, handles, and rubber frames (for bathrooms and offices) with the same previous quality. The price includes all requirements of handles, frames, shutters, of the Italian type (Yali), hinges, installation work, automatic closing arm (hydraulic), and floor bumpers for doors, provided that all work materials shall be of excellent quality and approved by the supervising engineer- ( unit- doors)		
44	<p>مفاقدة البوابات الرئيسية للمخازن بالمتر المربع مفاقدة - General building maintenance أبواب حديدية نوع كبس ويتم اعتماد العينة من قبل المهندس والتمن يشمل جميع مستلزمات العمل من حلوق وبراويز واطارات واللحام التثبيت والصنفرة والدهان ثلاثة اوجهة ضد الصدأ وثلاثة اوجهة بالون المطلوب ..... الخ لاكتمال العمل مع الاقفال وتغيير القطع المتهالكه وحسب تعليمات المهندس المشرف In square meters: Checking iron doors, press type and the sample shall be approved by the engineer. The price shall include all work requirements such as rings, frames, frames, welding, fixation, sanding and paint three sides against rust, and three sides in the required color .... etc to complete the work, with the locks and to change the worn out parts according to the engineer's instructions -(unit-2م Square Meter )</p>	EA	36
45	<p>اعمال الدهانات : بالمتر المربع : دهان املشن (شلد) للسقف - General building maintenance والجسور وبطن السلالم ثلاثة اوجهة لون ابيض للحضور على سطح مستوي وناعم مع استخدام المعجنه والتمن يشمل جميع مستلزمات الاعمال بحسب المواصفات وتعليمات المهندس المشرف Paints Works In square meter: Emulsion paint (shield) for the ceiling, bridges, and staircases, three sides, white color, to obtain a flat and smooth surface, with the use of paste. The price shall include all works requirements according to the specifications and instructions of the supervising engineer -(unit-2م Square Meter )</p>	meter	40
46	<p>توريد وتركيب وتشغيل انارة خارجية مع الاستفادة من - General building maintenance الاعمدة المتواجدة في ساحة المركز مع تمديد كابل 4 مم * 2 إضافة الى تركيب لوحة تحكم تعمل اثناء Supply, البيل خلية ضوئية بما يتناسب مع حجم الشبكة (تعمل بالكهرباء) او (بطاقة الشمسية installation and operation of external lighting, taking advantage of the columns located in the center square, with extension of a 4mm cable * 2, in addition to installing a control panel that works during the night, a photovoltaic cell commensurate with the size of the network (powered by electricity) or (solar energy).- (unit- حبة Piece )</p>	EA	50
47	<p>بالمتر المربع صيانة أرضية غرفة المولد والعمل يشمل - General building maintenance تلايبس وصبة خفيفة بسمك (10 ملم) على شكل بلاطات (3*3) وتعبئة الفواصل بخلاطة اسمنتية مرنة In square meter: Maintenance of the generator room floor. The work shall include coatings and light grouting with a thickness of (10 mm) in the form of tiles (3 * 3) and filling the joints with a flexible cement mixture, in additon to all necessary things and according to the instructions of the supervising engineer-(unit-2م Square Meter )</p>	meter	40
48	<p>مفاقدة السقف المعدني للورشه ويشمل العمل مفاقدة الزنك - General building maintenance وتغيير المتهالك من نفس المواصفات القديمة او ما يماثلها من نوعية ممتازة والجسور والمعدات واعمال الدهان للمعدات وقنوات تصريف المطر من افقيا ورأسية وتغيير العازل الحراري وشبك وتغيير المتهالك ويشمل العمل تغيير كل ما يلزم لسقف الورشه (الهنجر) وبحسب تعليمات المهندس المشرف Inspection of the metal roof of the workshop. It includes checking the metal zinc and changing the worn out with the same old specifications or similar ones, of excellent quality, and aslo checking the bridges and purlins, painting works for the purlins and rain drainage channels both horizontally and vertically, and changing the damaged thermal insulation and grilles. Also the work includes</p>	EA	185



	changing everything necessary for the roof of the workshop (hanger) according to instructions of the supervising engineer-(unit-2م Square Meter )		
49	<p>General building maintenance - بالمترالمربع توريد وتركيب شبابيك (نافذة المونيوم) نوع - ايطالي او ما يعادله بالون المطلوب المسقول نوعية لوفر على ان يتم الفتح والغلق الى اعلى واسفل بذراع مثبت على الجدران بمقبض غير قابل للصداء سمك الالمونيوم (1.4 ملم) على ان يعتمد اللون والقطاعات والمفصلات والمقابض نوع ايطالي وجميع المستلزمات الاكسسوارات قبل عملية التوريد والتصنيع وطبقا للمواصفات السابقة والتمن يشمل عمل شبك واقى من الحشرات والبراويز والاطارات المطاطية ويكون سمك الزجاج (6ملم) شفاف ومعتم على ان تكون اعمال الالمونيوم كاتمه تماما لمنع تسريب المياه وتيار الهواء مع مفاقدة شبك الحماية ودهانه بدهان مقاوم للصداء ودهان خاص بالحديد In square meter: supply and installation of windows (aluminum window) Italian type or its equivalent in the required color, polished type of Louvre, provided that the opening and closing are done up and down with an arm fixed to the walls with a stainless handle. Aluminum thickness is (1.4 mm), provided that the color, sectors, hinges and handles are Italian type and all supplies and accessories shall be approved before the supply and manufacturing process, and according to the previous specifications. The price shall include the work of protective nets from insects, frames and rubber , and the thickness of the glass is (6 mm) transparent and opaque, provided that the aluminum works shall be completely perfect to prevent water leakage and air current, with checking protection nets and painted them with anti-rust paint and a special iron paint, according to the instructions of the supervising engineer-(unit-2م Square Meter )</p>	meter	3.50
50	<p>General building maintenance - بالمترالمربع توريد وتركيب شبابيك المونيوم نوع ايطالي او ما يعادله بالون المطلوب المسقول نوعية ممتازة سمك الالمونيوم (1.4ملم) على ان يعتمد اللون والقطاعات والمفصلات والمقابض (نوع ايطالي) وجميع المستلزمات والاكسسوارات قبل عملية التوريد والتصنيع وطبقا للمواصفات السابقة وتعليمات المهندس المشرف والتمن يشمل عمل شبك واقى من الحشرات والبراويز والاطارات المطاطية ويكون سمك الزجاج (6ملم) شفاف ومعتم للحمامات على ان تكون اعمال الالمونيوم كاتمه تماما لتسريب الماء وتيار الهواء واستخدام مادة السليكون للفراغات ومفاقدة شبك حماية للنوافذ مع الصنفرة ودهان بريمر وجهين ووجهين بالون المطلوب والتببيت In square meter: Supplying and installation of aluminum windows, Italian type, or its equivalent, in the desired color, polished, excellent quality, aluminum thickness (1.4 mm). The color, sectors, hinges, handles (Italian type) and all supplies and accessories shall be approved before the supply and manufacturing process, and according to the previous specifications and the instructions of the supervising engineer. The price shall include making protection insects grilles , in addition to the frames and rubber ,and thickness of the glass should be (6 mm), transparent and opaque for bathrooms. The aluminum works shall be completely perfect to prevent leakage of water and air current, with using silicone material for spaces, and also checking windows protection grilles, with sanding and primer paint two sides in the required color, besides gluing and welding, and replacing worn and damaged ones, -(unit-2م Square Meter )</p>	meter	4
51	<p>General building maintenance - بالعدد مفاقدة وصيانة شبابيك (نوافذ) المونيوم - فردتينويشمل اصلاح او استبدال التالف من عناصر النوافذ من مغالق المفصلات المقابض واطار الحلق والدرف وزجاج سمك (6ملم) وشبك النامس والريالات والخردوات وتعبئة الفراغات بمادة السليكون للنوافذ الالمونيوم نوعية كاتمه وبحسب النوع واللون والمواصفات الموجودة سابقا وتثبيت الجيد In number: Checking and maintenance of aluminum windows, two pieces, and it includes repairing or replacing the damaged windows elements such as shutters of the hinges, the handles, the frame of the edge, glass of thickness is (6 mm),</p>	EA	144.

	including the mosquitos mesh, the straps, the hardware, and filling the gaps with silicone material for the aluminum windows, They shall be of the silencer quality, and according to the type , color, and specifications previously available. In addition to fixing the good with scroop nails not less than (5 cm) in length , and making all necessary things to complete the work, as per the instructions of the supervising engineer-(unit-number of windows )		
52	General building maintenance - بالمتري المربع توريد وتنفيذ طرطشة اسمنتية ملونة ترش البيا - من مواد مقاوم للعوامل الجوية للواجهات الخارجية بحسب المواصفات السابقة وتقديم عينة للمهندس In square meter: Supplying and implementing a colored cement spraying that is automatically sprayed from weather-resistant materials for the external facades, according to the previous specifications, and submitting a sample to the engineer and according to the instructions of the supervising engineer -(Unit-2م Square Meter )	meter	110
53	General building maintenance - توريد طبلون رئيسي 600 امبير مع عدد 2 قواطع 200 امبير و عدد 2 قواطع 150 امبير و عدد 8 قواطع 100 امبير متكامل من مستلزمات لمبات البيان وساعات مراقبة Supplying of a 600-amp main panel with two circuit breakers (200-amp), two circuit breakers (150amp), and eight circuit breakers (100 amp), complete with supplies for indication lamps and monitoring clocks-(unit- حبة Piece )	meter	1
54	General building maintenance - بالمتري الطولي توريد وتركيب مواسير حديد مجلفن قطر 4هنش صرف مياه الامطار حتى منسوب الرصيف او اقرب مصرف لمياه المطر في الموقع شامل الجار جوري من الالومنيوم او من مواد غير قابله للصدء مع جميع الملحقات الخاصة به والتثبيت على In linear meter: Supply and installation of galvanized iron pipes of 4 inch diameter, rain water drainage up to the level of the pavement or the nearest rain water drain at the site, including a drain made of aluminum or of non-rusting materials with all its accessories, and installation at the vertical level to the level of the pavement according to the instructions of the supervising engineer-(unit-م/ط Linear/meter)	meter	4
55	General building maintenance - بالمتري المربع دهان مقاوم للرطوبة والعوامل الجوية استخدام - خارجي للذروه وبحسب المواصفات وتعليمات المهندس المشرف والتمن يشمل جميع مستلزمات In square meter: The paint shall be resistant to moisture and weather conditions. External use to the peak, according to the specifications and the instructions of the supervising engineer. The price shall include all work requirements -(unit-2م Square Meter	meter	30
56	General building maintenance - بالمتري المربع معالجة الخرسانة المسلحة للاعمدة في سقف المبنى الرئيسي وعمل تلابيس اسمنتية مع اعمال السكرية وإزالة الأجزاء المتهاكلة والمتصدعه للصبيات In square meter: Treatment of the reinforced concrete for the columns in the roof of the main building, and making cement coatings, with scrubs works, and removal of the dilapidated and cracked parts of the reinforced casting, according to the instructions of the supervising engineer-(2م Square Meter )	meter	8
57	General building maintenance - كابل أبو 16مم 4* نحاس فلكس على ان يتم تمديد من mm Cable * 4 الطبلون الرئيسي الي الطبلونات الفرعية في المخازن والورشه وغرفة المولد / 16 copper flex, provided that it is extended from the main panel to the sub panels in the stores, workshop and generator room -(unit-متر Meter)	EA	350
58	General building maintenance - البوابة الرئيسية للسور: توريد تركيب بواب حديدية للسور - فرتين بابعد (6.20*4) ومرايع (3*6)سم راسيا بصورة فنية ممتازة مع عمل شلمان دائري (5*5)سم واطار البوابة شلمان مقاس (7.5*7.5)سم وسمك 2مم ويتم تثبيت باربع نقاط من كل الجوانب	EA	1

	بواسطة قطع حديد سقائن مقاس (15*15) سم وسماك 6 مم تلحم عليها اسياخ حديد طول 15 سم تثبت باسياخ الاعمدة ويلحم اطار البوابة عليها ويشمل كل مايلزم من تثبيت وتركيب واقفال والدهانات Main gate of the fence Supplying the installation of iron gate for the fence, two sides with dimensions (4*6.20) and squares (6 *3) cm vertically, in an excellent artistic way, with making a circular shalman work (5 * 5) cm, and the frame of the gate shall be shalman, size (7.5 * 7.5) cm and a thickness of 2 mm, and it shall be fixed with four points from all sides by pieces of cast iron, size (15 * 15) cm and 6 mm thick. Iron skewers of 15 cm in length shall be welded to it and to be fixed to the skewers of the columns. Thhis shall include all necessary things such as fixing, installation and locks in addition to the anti-rust paints, and 3-sided oil paint in the required color, according to the instructions of the supervising engineer -(unit-number of gate)		
59	اعمال الدهانات : بالمترالمربع : دهان املشن (شلد) للسقف والجسور وبطن السلالم ثلاثة اوجه لون ابيض للحصو على سطح مستوي وناعم مع استخدام المعجنه والتمن يشمل جميع مستلزمات الاعمال بحسب المواصفات وتعليمات المهندس المشرف Paints Works In square meter: Emulsion paint (shield) for the ceiling, bridges, and staircases, three sides, white color, to obtain a flat and smooth surface, with the use of paste. The price shall include all works requirements according to the specifications and instructions of the supervising engineer-(unit-2م Square Meter )	meter	1,220
60	General building maintenance - تركيب تشغيل سكين 800 امبير اربع بول (CHANGEOVER) بحيث يتم تركيبها في غرفة المولد وربطها بكابل 240 مم* 4 من المولد بطول المناسب ويشمل ذلك Installation of a 800-amp four-pole switch (CHANGEOVER) to be installed in the generator room and connected to a 240 mm * 4 cable from the generator in an appropriate length. This includes installation,wickering, isolation and fixation of an iron base for a knife/switcher- (unit- مقطوعة Piece Work)	EA	1
61	General building maintenance - كابل أبو 2.5 مم مفرد احمر+ اسود + اصفر 1.5 مم نحاس - فلكس على ان يتم تمديد من الطبلونات الفرعية في المبنى الى الأقسام والغرف والمكاتب للمأخذ 2.5 ( فيشات ) mm Cable, single, red + black + yellow 1.5 mm copper flex provided that it is extended from the sub-drums/panels in the building to the departments, rooms and offices of the electrical outlet (plugs) - 20 - اسود، 20 احمر، 10 اصفر Red20,black20,yellow10 -(unit- حبة Piece	EA	50
62	General building maintenance - مفاتيح كهرباء 2 خط يتم تركيبها في الغرف والمكاتب line electric switches to be installed in rooms, offices and stores-(unit- حبة Piece )	EA	60
63	General building maintenance - تركيب وتشغيل طبلون رئيسي 100 امبير مكون متعدد 24 قاطع أبو 30 و 20 و 16 و 10 امبير يشمل ذلك ربط الكابلات الفرعية في موقع الطبلون والتكسير وتعديل موقع الطبلون وتثبيت إضافة الى إعادة سحب الكابلات من الأقسام والغرف بكابلات المحددة Installation and operation of a 100-amp main panel, consisting of 24 breakers ( 30, 20, 16, and 10 amps). This includes connecting the sub-cables at the panel site, breaking, adjusting the panel location, and installing, in addition to re-pulling cables from sections and rooms with cables specified according to the type of cable (1.5 mm for lighting and 2.5 mm for the plug socket, and 4 mm for air conditioners)- (unit- حبة Piece )	EA	4

64	General building maintenance - Ceiling fans with regulator- (unit- حبة- Piece )	EA	21
65	General building maintenance - تركيب أرضية عازلة مقاومة للصدمات لمخزن الادوية ومخزن المبيدات Installing a shock-resistant insulated floor for the medicine and the insecticides stores-(Unit- 2م Square Meter )	EA	559
66	General building maintenance - توريد سكين 800 امبير ايتوماتيكي اربع بول (CHANGEOVER) Supplying an 800-amp automatic four-pole switch (CHANGEOVER) with galvanized copper poles-(unit- حبة- Piece )	EA	1
67	General building maintenance - توريد كابل 240 مم * 4 نحاس مسلح Supplying a cable 240 mm * 4 reinforced copper-(unit- متر Meter)	EA	120
68	General building maintenance - مفاقدة اعمال نوافذ الالومنيوم لمخازن المبيدات والمرشات بالعدد تغيير الزجاج المكسر لجميع نوافذ المخازن نفس المواصفات القديمة مع مراعاة ومفاقدة المقابض والبيدات والريالات وجميع الخردوات والاكسسوارات ومايلزم لاتمام العمل مع مفاقدة شبك الحماية لجميع النوافذ للمخازن ويشمل الدهانات البريمر والدهانات الزيتي والتثبيت والتلحيم وحسب Inspection of aluminum windows for the insecticides and sprayers warehouses In number: changing the broken glass for all the windows of the warehouses, with the same old specifications, taking into account to check handles, straps, all hardware and accessories, and what is necessary to complete the work, in addition to checking the protective grilles for all windows of the warehouses, and it includes primer paints, oil paints, fixing and welding, and according to the instructions of the supervising engineer-(unit-number of windows )	EA	23
69	General building maintenance - بالمترالمربع مباني بلك (بردين) اسمنتي اتوماتيكي مصمت (20*20*40) بسمك 20 سم بالمونة الاسمنتية بنسبة 3:1 للصور على ان يكون البناء منظمًا ومستوي بناء بالقدة والميزان على ان لا تقل سماكة المونة عن 2 سم ومقاونة البلك المصمة المطلوب (45) كجم/سم مع عمل كابلات (40*40) سم للاماكن المتضررة والمهدومة خلف مبني المخازن مع إعادة بني الكرنيش وتلبس العمود الكورنيش بجحر اخضر منشار بنفس المواصفات الاولى في ركن الحوش By square meter, the fence shall be built with automatic solid cement blocks (20 * 20 * 40), 20 cm in thickness, with cement mortar at a ratio of 3:1 for the wall. The building shall be organized and levelled based on the measure and scale, and thickness of mortar shall not be less than 2 cm, and resistance of the required solid block shall be (45) kg/CM2, with making caps (40 * 40) cm for the damaged and demolished places behind the warehouses building, with re-building the cornice, and cladding the cornice column with green sawn stone with same first specifications in the corner of the yard in accordance to the instructions of the supervising engineer-(unit- 2م Square Meter	meter	4
70	General building maintenance - بالمترالمربع دهان زيتي نصف لمعه للقواطع الداخليه والجدران والاعمدة دهان زيتي نصف لمعه (شلد) نوعية معتمده من قبل المهندس ثلاثة أوجه مع المعجنه والصنفرة وطبقة الأساس للحصول على سطح مستوي وناعم وبألون المحدد حسب تعليمات المهندس In square meter: Semi-glossy oil paint for interior partitions, walls and columns with semi-glossy oil paint (Shield), quality approved by the engineer, on three sides with paste and sanding and base coat to obtain a flat and smooth surface in the needed color according to the instructions of the supervising engineer. The price shall include all work requirements-(unit- 2م Square Meter )	meter	2
71	General building maintenance - صيانة حوض تربية الأسماك الموجود في فناء المحور، صيانة Maintenance of the fish الأرضية والجدران وعمل شبك حديد على سقف الحوض مقاوم للصدمات	EA	1

	breeding tank(aquarium) located in the courtyard, in addiiton to maintenance of the floor and walls, and construction of an iron grille on the aquarium roof, which shall be resistant to rust (unit- number aquarium)		
72	General building maintenance - <i>توريد وتركيب طبلون فرعي بقاطع رئيسي 100 امبير ثلاثة فاز - Supply and installation of a sub-panel with a main breaker of 100 amps, three phases, and 24 sub-breakers of 30, 25, 20, and 16 amps.-(unit- حبة Piece )</i>	EA	4
73	General building maintenance - <i>أبواب المونيوم لغرفة الحراسة بالمترالمربع توريد وتركيب أبواب المونيوم بقطاع لا يقل عن (10سم) إيطالي وعمل الواح كبس (ميلامين) مغطاء بشرايح المونيوم المسقول درجة أولى وبعد اعتماد القطاعات للحلوق والمقابض والاطارات المطاطية وزجاج سمك (8ملم) مسلح نصف شفاف والتمن يشمل جميع المستلزمات من المقابض والبراويز والمغالق نوع يالي ايطالي ومفصلات واعمال التثبيت وذراع الاغلاق التلقائي (هيدروليكي) للابواب على ان تكون كل مواد العمل نوعيه ممتازة ومعتمده من قبل المهندس طبقا للمواصفات السابقة وعلى ان تكون الملحقات Aluminum doors for the guards room is in square meters: Supply and installation of aluminum doors with a sector of not less than (10 cm) Italian, and making press plates (melamine) covered with first-class polished aluminum slices. The rings sectors, handles, rubber frames and glass thickness (8 mm) armed semi-transparent shall be approved prior to supply. The price shall include all requirements of handles, frames, and shutters of the Italian type, hinges, fixing works, and automatic (hydraulic) closing levers for doors, provided that all working materials are of excellent quality and approved by the engineer according to the previous specifications, and the accessories shall be rust-resistant-(unit-2م Square Meter</i>	EA	2
74	General building maintenance - <i>تركيب وتشغيل طبلون رئيسي 600 امبير مكون من عدد 4 قواطع 150 امبير و عدد 8 قواطع 100 امبير يشمل ذلك ربط الكابلات الفرعية في موقع الطبلون Installation والتكسير وتعديل موقع الطبلون وتثبيت وتلحيم قاعدة حديد بما يتناسب مع الطبلون and operation of a 600-amp main panel consisting of four circuit breakers (150-amp) and eight circuit breakers (100-amp). This includes connecting the sub-cables at the panel site, breaking and adjusting the panel site, installing and welding an iron base to suit the panel -(unit- مقطوعة Piece Work)</i>	EA	1
75	General building maintenance - <i>بالمترالمربع دهان مقاوم للرطوبة والعوامل الجوية استخدام خارجي للذروه وبحسب المواصفات وتعليمات المهندس المشرف والتمن يشمل جميع مستلزمات In square meter: The paint shall be resistant to moisture and weather conditions, for external use to the peak, according to the specifications and instructions of the supervising engineer. The price shall include all work requirements -(unit-2م Square Meter )</i>	meter	20
76	General building maintenance - <i>بالمترالطولي :مفاقدة مجاري داخلية انايبب حديد زهر او بلاستيك والتمن يشمل التكسير ان لزم الامر والاعادة من نفس المواد السابقة وتغيير مواسير المجاري التالفة في الموقع ان وجد ويشمل الردم تحت وفوق المواسير من الطبقة الناعمة (UPVC) ضغط عالي سريلا تقل 30سم بالإضافة الى اعمال الردم للتربة الصالحة للردم بحسب ماسيب الموقع مع الدك والرش على طبقات مع مراعاة الميول طبقا للمواصفات مع مفاقدة جميع المواسير من الحمامات الى غرف التفتيش الى البيرة وحسب تعليمات المهندس المشرف مواسير :- 4 هنش م/ط = 8, 6هنش In linear meter: Inspection of the internal sewers, cast iron pipes or plastic. The price shall include cracking, if necessary, and re-use of the same previous materials, and changing high-pressure sewer pipes (UPVC) for the damaged at the site, if any, and it includes also backfilling under and above the pipes from the soft layer of not less than 30 cm, in addition to</i>	meter	50

	backfilling works for the suitable soil according to the site's requirements with tamping and spraying on layers taking into account the inclinations according to the specifications, with inspection of all pipes from the bathrooms to the manholes and to the sewer, and as per the the instructions of the supervising engineer Pipes: - 4 inch I/m = 8 6 inch I/m = 170 8 inch I/m = 30 (unit-ط/م Linear/meter)		
77	General building maintenance - بالمتر المكعب اعمال الصب (صبية خرسانه خفيفة التسليح - لزوم الارضيات بمقاومة لا تقل عن (200 كجم/سم2) بنفس المواصفات السابقة حتى تستوي مع الطبقات القديمة ومعالجة جميع الشروخ في الصببات باستخدام اسمنت بورتلاندي مقاوم للاملاح والكبريتات ويشمل العمل المواد وجميع مستلزمات التنفيذ وبحسب السماكة القديمة وتعبئة الفواصل In cubic meter: casting works (lightly reinforced concrete pouring) for the floors with a resistance of not less than (200 kg/CM2), with the same previous specifications in order to be in the level with the old layers. In addition to treating all cracks in the castings using Portland cement that is resistant to salts and sulphates. The work shall include materials and all work requirements according to the previous old thickness, and filling the joints with a flexible cement mix-(unit-3م Cubic meter	meter	11
78	General building maintenance - عمل : تمديد وتركيب كابل 240 مم * 4 مسلح على ان يتم ربطه من السكنين القلاب في غرفة المولد وتمديده تحت الأرض بعمق 70 سم وتوصيلة الي الطبلون Making an extension and installation of a 240 mm * 4 -reinforced cable, provided that it shall be tied from the tipping knife in the generator room and extend it underground at a depth of 70 cm, and connecting it to the main center electricity-panel, with securing the the requirements of the linking and fixing process in terms of wicker for shearing and insulation-(متر Meter)	EA	120
79	General building maintenance - بالمتر المكعب صبة خرسانه مسلحة لارضية الساحة خرسانه خفيفة التسليح اسمن مقاوم للاملاح 200 كجم /سم2 باسخدام اسمنت المقاوم للاملاح على ان لا يقل عدد الاسياخ عن 5 ق أبو 12/م في الاتجاهين فرش وغطاء وسمك حسب الخرسانة القديمة وإن تكون مستوية مع الصبة القديمة ويشمل التخشبية , توريد وقص ووضع الحديد , الصب , الرش وكل مايلزم In cubic meters, pouring a reinforced concrete for the yard floor. The concrete is to be lightly reinforced concrete, salt resistant cement 200 kg/Cm2 In cubic meter, supplying and installing lightly reinforced concrete with a resistance of not less than 200 kg/Cm2 using salt-resistant cement, provided that number of skewers is not less than 5 sq, 12/m in both directions. Brushing, covering and thickness according to the old concrete, and shall be levelled with the old casting, including lumber, supplying, cutting and laying iron, casting, spraying and all necessary things, as per instructions of the supervising engineer (unit-3م Cubic meter)	meter	3
80	General building maintenance - مفاقدة اعمال نوافذ الالومنيوم لورشة صيانة السيارات بالعدد تغيير الزجاج المكسر لجميع نوافذ المخازن نفس المواصفات القديمه مع مراعاة ومفاقدة المقابض والبيدات والريالات وجميع الخردوات والاكسسوارات ومايلزم لاتمام العمل مع مفاقدة شبك الحماية لجميع النوافذ للمخازن ويشمل الدهانات البيرمر والدهانات الزيتي والتثبيت والتلحيم ومع Inspecting the aluminum windows of the car maintenance workshop By number, changing the broken glass for all the windows of the stores, the same old specifications, taking into account and inspecting the handles, handles, straps, all hardware and accessories, and what is necessary to complete the work, with the inspection of the protection grilles for all windows of the stores, including primer paints, oily paints, fixing and welding, and with the inspection of the	EA	4



	protection grilles from sanding, paints and fixing, according to the instructions of the supervising engineer - (2م Square Meter )		
81	General building maintenance - كابيل أبو 25 مم * 4 نحاس فلكس على ان يتم تمديد من - mm * 4 copper flex cable, provided that it should be extended from the main panel to the sub panels in the building (unit-متر Meter)	EA	50
82	General building maintenance - بالمتر المربع دهان مقاوم للرطوبة والعوامل الجوية استخدام - خارجي للذروه وبحسب المواصفات وتعليمات المهندس المشرف والتمن يشمل جميع مستلزمات In square meters: paint is resistant to moisture and weather conditions. External use to the peak, according to the specifications and the instructions of the supervising engineer. The price shall include all work requirements-(unit-2م Square Meter )	meter	70
83	General building maintenance - بالمقطوعة مفاقدة وصيانة القبة الفيبرجلاس من تلابيس - In piece work: Checking and maintaining the fiberglass dome in terms of the panels and paints, and also checking the cornice as per the instructions of the supervising engineer -(unit-مقطوعة Piece Work )		1
84	General building maintenance - بالمتر المربع دهان زيتي نصف لمعه للقواطع الداخليه - والجدران والاعمدة بدهان زيتي نصف لمعه (شلد) نوعية معتمده من قبل المهندس ثلاثة أوجه مع المعجنه والصفرة وطبقة الأساس للحصول على سطح مستوي وناعم وبألون المحدد حسب تعليمات المهندس المشرف والتمن يشمل جميع مستلزمات الاعمال In square meter: semi-glossy oil paint for interior partitions, walls and columns with semi-glossy oil paint (Shield) quality approved by the engineer on three sides with paste , sanding and base coat to obtain a flat and smooth surface and in the specified color according to the instructions of the supervising engineer and the price includes all work requirements-(unit-2م Square Meter )	meter	900
85	General building maintenance - بالمتر المربع المفاقدة والصيانة للسقف المعلني زنك امريكي - لمظلة موقف السيارات باستبدال كل البهر المذحلة والمتاكلة والتالفة ببهر سماكة 50 جيز لون بني مع عمل عازل سعودي سمك 2 سم مع توريد وتركيب شبك حسب الابعاد شاملا اعمال الفك والتركيب او الصفرة ورش برير 3 اوجهه والدهان الزيتي 3 اوجهه للهنجر والجسور والمدادات والاعمده بالكامل In square meter: Inspection and maintenance of the metal roof, American zinc, for the car park canopy, and replacing all worn out, corroded and damaged pieces with other pieces of thickness 50 giz, brown color, with making a Saudi insulation (2 cm thickness). In addition, supplying and installing nets according to the dimensions, and it includes works of dismantling, installation, sanding and primer spraying 3 faces, and oil paint 3 faces for the hanger, bridges, piers, and columns completely, and also installing rainwater gutters with changing bridges, purlins, and worn out and damaged columns-(unit-2م Square Meter )	meter	650
86	General building maintenance - توريد وتركيب وتشغيل انارة داخلية فلبس 23 وات ليد - Supply, installation and operation of internal lighting, 23 watt LED, for all rooms, departments and stores-(unit-حبة Piece )	EA	130
87	General building maintenance - توريد وتركيب مرحاض شرقي رقية كاملة نوعية ممتازة شاملا - صندوق الطرد سعة (2.5 جالون بلاستيك) من نفس لون المرحاض + حنفية وضوء منفصلة مع لي Supplying and installing an oriental full neck toilet of excellent quality, including a flush box (2.5 gallon, plastic) of the same	EA	4

	toilet color + a separate faucet for ablution, and also with a water hose fixed to a chrome wall + a paper holder - (unit- toilet )		
88	General building maintenance - كابل أبو 1.5 مم مفرد احمر + اسود + اصفر نحاس فلكس mm على ان يتم تمديد من الطبولونات الفرعية في المبنى الى الأقسام والغرف والمكاتب اناة 1.5 Cable, single, red + black + yellow copper flex, provided that it is extended from the sub-panels in the building to the departments, rooms and offices for lighting-(unit- حبة Piece )-20 اصفر 10، اسود، 20 احمر، Red20,black20,yellow10	EA	50
89	General building maintenance - بالعدد مفاقدة بوابة الثانية للورشة ويشمل العمل من دهانات مانعه للصداء (بريمر) ثلاثة اوجهة والصفرة ودهانات زيتي خاصة بالحديد ثلاث اوجهة ومفاقدة او تغيير المفصلات والحلوق والاطارات والبراويز وتغيير اقفال جديدة نوعية ممتازة وكل مايلزم لاتمام In number: Checking the second gate of the workshop, and the work includes anti-rust paints (Primer), three sides, sanding, and oil paints for iron, three sides, and checking also or changing hinges, rings, and frames, and changing new locks of excellent quality, and all necessary things to complete the work, according to the instructions of the supervising engineer-(unit-number of gate)	EA	10
90	General building maintenance - تركيب وتشغيل طبلون رئيسي 63 امبير مكون عدد عدد 18 قاطع أبو 30 و 20 و 16 و 10 امبير يشمل ذلك ربط الكابلات الفرعية في موقع الطبلون والتكسير وتعديل موقع الطبلون وتثبيت إضافة الى إعادة سحب الكابلات من الأقسام والغرف بكابلات المحددة Installation and operation of a 63-amp main panel, consisting of 18 breakers (30, 20, 16, and 10 amps). This includes connecting the sub-cables at the panel site, breaking, adjusting the panel site, and installing, in addition to re-pulling the cables from the sections and rooms with the cables specified according to the type of cable( 1.5 mm for lighting, 2.5 mm for the outlet Plugs and 4 mm for air conditioners)- (unit- مقطوعة Piece Work)	EA	5
91	General building maintenance - باب حديدي مجلفن (2 ملم) لمدخل جانبي للمبنى الرئيسي بالعدد توريد وتركيب باب حديد مجلفن (2 ملم) درفتين لبوابة جانبية للمدخل المبنى الرئيسي بابعاد (2*1.1) والسعر يشمل الطلاء (طبقة أولية بالإضافة الى طلائين معجون وصفرة) (ماركه معتمدة) ومفصلات ومقابض والقيام بكل ما هو مطلوب لانتهاء العمل وبحسب تعليمات المهندس المشرف Galvanized iron door (2 mm) for a side entrance to the main building In number: Supplying and installing a galvanized iron door (2 mm) with two shutters for a side gate of the entrance to the main building with dimensions (2*1.1). The price includes paint (a primer coat in addition to two putty and sanding paints (an approved brand), hinges and handles, and doing everything required to finish the work and according to the instructions of the supervising engineer - (unit-doors)	EA	1
92	General building maintenance - بالعدد توريد وتركيب بوابة حديد فردتين (لوفر) درجة اولي لورشه صيانه السيارات وبعد اعتماد العينات من قبل المهندس والتمن يشمل جميع المستلزمات من مغالق ومفصلات وحلوق وبراويز واطارات واقفال وجميع اعمال اللحام والتثبيت والصفرة والجلي والجلخ والدهان المانع للصداء ودهان عازل وجميع مستلزمات العمل وبحسب المواصفات القديمة In number: Supply and installation of a two-pieces iron gate (Louvre), first class, for the vehilces maintenance workshop, and after approving the samples by the engineer. The price shall include all requirements such as bolts, hinges, rings, frames, locks, and all welding, fixing, sanding, polishing, abrasive, anti-rust paint, insulating paint, and all work requirements according to the old specifications, in addition to fixing corners of the destroyed gates, according to the instructions of the supervising engineer-(unit-number of gate)	EA	1



93	General building maintenance - صيانة ومفاقدة الببارة وكل ما يلزم للببارة من غطاء وغيره Maintenance and check the sewer and all its needs in terms of the cover and other things -(unit-Number sewer		1
94	General building maintenance - مفاقدة شبك الحماية للنوافذ للمبنى الرئيسي: بالعدد مفاقدة - شبك الحماية للنوافذ الالومونيوم للمبنى الرئيسي الدور الأرضي ويشمل البند اعمال اللحام والتثبيت والجلخ والجلي والمعجنه الخاصة بالحديد والصنفرة والسقل إضافة الى الدهان بالاعمال الحديدية المانعه للصداء وباللون المعتمد من المهندس المشرف والتمن يشمل جميع العمال والمواد والادوات وجميع ما يلزم لانهاء العمل وبحسب المواصفات السابقة وبحسب تعليمات المهندس المشرف Checking windows protection grills for the main building In number: Checking protection grille for the aluminum windows of the main building, the ground floor. It includes welding, fixing, grinding, polishing, iron kneading, sanding, and scaling, in addition to painting with anti-rust iron works and in the color approved by the supervising engineer. The price shall include all works and materials and items needed to complete the works as per the previous specifications and as per the instructions of the supervising engineer -(unit-number windows)	EA	150
95	General building maintenance - بالمترالمربع دهان زيتي نصف لمعه للقواطع الداخليه - والجدران والاعمدة بدهان زيتي نصف لمعه (شلد) نوعية معتمده من قبل المهندس ثلاثة أوجه مع المعجنه والصنفرة وطبقة الأساس للحصول على سطح مستوي وناعم وباللون المحدد حسب تعليمات المهندس المشرف In square meter: Semi-glossy oil paint for interior partitions, walls and columns with semi-glossy oil paint (Shield), quality approved by the engineer, three sides with putty, sanding and base coat to obtain a flat and smooth surface and with the specified color according to the instructions of the supervising engineer. The price shall include all works requirements-(unit-2م Square Meter )	meter	90
96	General building maintenance - اعمال الدهانات : بالمترالمربع : دهان : املشن (شلد) للسقف والجسور ويطن السلالم الثلاثة اوجهة لون ابيض للحصول على سطح مستوي وناعم مع استخدام المعجنه والتمن يشمل جميع مستلزمات الاعمال بحسب المواصفات وتعليمات المهندس المشرف Guards' Room Paints' Works In square meters: Emulsion paint (shield) for the ceiling, bridges, and belly of the three staircases, white color faces, to get a flat and smooth surface, with using paste. The price shall include all works requirements according to the specifications and instructions of the supervising engineer -Unit-(2م Square Meter )	meter	40
97	General building maintenance - Supply, توريد وتركيب وتشغيل مكيفات طن ونصف installation and operation of one and a half ton air conditioners -(unit- حبة Piece )	EA	12
98	General building maintenance - بالمترالمربع توريد وتنفيذ طرطشة اسمنتية ملونة ترش البيا - من مواد مقاوم للعوامل الجوية للواجهات الخارجية بحسب المواصفات السابقة وتقديم عينة للمهندس المشرف In square meter: Supplying and implementing a colored cement spraying that is automatically sprayed from weather-resistant materials for the external facades, according to the previous specifications, and submitting a sample to the engineer and according to the instructions of the supervising engineer -(unit-2م Square Meter )	meter	150
99	General building maintenance - توريد وتركيب طبلون فري بقاطع رئيسي 63 امبير ثلاثة فاز - Supply and installation of a sub-panel with a main breaker of 63 amps, three phases, and 18 sub-breakers of 30, 25, 20, and 16 amps.-(unit- حبة Piece )	EA	5

100	<p>General building maintenance - بالمترالمربع دهان زيتي نصف لمعه للقواطع الداخليه - والجدران والاعمدة بدهان زيتي نصف لمعه (شلد) نوعية معتمده من قبل المهندس ثلاثة أوجه مع المعجنه والصنفرة وطبقة الأساس للحصول على سطح مستوي وناعم وباللون المحدد حسب تعليمات المهندس In square meter: Semi-glossy oil paint for interior partitions, walls and columns with semi-glossy oil paint (Shield), quality approved by the engineer, three sides with putty, sanding and base coat to obtain a flat and smooth surface and in the specified color according to the instructions of the supervising engineer. The price shall include all work requirements -(unit- 2م Square Meter )</p>	meter	150
101	<p>General building maintenance - مفاقدة جميع الابواب المونيوم وباب حديد حماية لغرفة امين الصندوق بالعدد مفاقدة ابواب المونيوم للمبنى الرئيسي ويشمل اصلاح او استبدال التالف من عناصر الأبواب ان وجدت (المفصلات والمغاليق والحلوق والدرف والربلات والمقابض والاقفال والاطارات المطاطية) وتعبئة الفراغات بمادة السليكون والتثبيت الجيد واستخدام الخواير والسكاريب Checking بطول لا يقل عن (5سم) وجيع مايلزم لانهاء العمل وبحسب تعليمات المهندس المشرف all aluminum doors, and an iron door to protect the treasurer's room In number: Checking aluminum doors for the main building, including repairing or replacing damaged door elements, if any (hinges, shutters, rings, bars, handles, locks, and rubber frames) and filling the spaces with silicone, good fixing, using cotter pins and screws with a length of not less than (5 cm), and making all necessary things to complete the work, and according to instructions of the supervising engineer-(unit-number of doors)</p>	EA	26
102	<p>General building maintenance - بالعدد مفاقدة باب حديد كريتل مع تغيير الزجاج - المسلح(10 ملم) ويشمل الحلوق والقوائم الراسية والعرضية الحديد المسقول من القطاعات الحديدية المصمته (12ملم, 14ملم) ومفصلات ومغاليق (نوع اربعة مخارج) والصنفرة والدهان مانع للصداء والدهان النهائي من نفس النوع المستخدم للسيارات نفس النوع السابق وذراع الغلق التلقائي وجميع In number: Checking a crytal iron door and changing the reinforced glass (10 mm), including rings, vertical and transverse posts, wrought iron from solid steel sectors (12 mm, 14 mm), hinges and shutters (four exits type), sanding, anti-rust paint, and the final paint of the same type used for cars, the same previous type, and an automatische locking lever, in addition to all requirements, according to the instructions of the supervising engineer-(unit-number of doors)</p>	EA	1
103	<p>General building maintenance - بالعدد توريد وتنفيذ نوافذ المونيوم فردتين نوع ايطالي باللون المطلوب المسقول نوعية ممتازة سمك الالمونيوم (1.8ملم) على ان يعتمد اللون والقطاعات والمفصلات والمقابض نوع ايطالي وجميع المستلزمات والاكسسوارات قبل عملية التوريد والتصنيع حسب المواصفات السابقة والتمن يشمل عمل شبك واقى من الحشرات والبراويز والاطارات المطاطية ويكون سمك الزجاج (6ملم) شفاف ومعتم وعلى ان تكون اعمال الالمونيوم كاتمته تماما لتسريب الماء In number: Supply and implementation of aluminum windows, two pieces, Italian type, in the required color, polished, excellent quality, aluminum thickness (1.8 mm).The color, sectors, hinges and handles shall be of Italian type, and all supplies and accessories shall be approved before the supply and manufacturing process, and shall be according to the previous specifications. The price shall include making protective grills, frames, rubber, and thickness of the glass shall be (6 mm), transparent and opaque. The aluminum works must be completely impervious to water leakage and air current, according to the instructions of the supervising enginee-(unit-number of windows)</p>	EA	6

104	General building maintenance - <i>توريد وتركيب وتشغيل مكيفات 2 طن خاصة بالمخازن</i> Supply, installation and operation of 2-ton air conditioners for warehouses- (unit- حبة Piece )	EA	6
105	General building maintenance - <i>تركيب وتشغيل كابل نحاس أبو 16 مم * 4 فلكس على ان يتم</i> <i>ربطة من الطبلون الرئيسي الى مبنى التغذية وتمديده تحت لأرض بعمق 50 سم ويشمل ذلك عملية</i> Installation and operation of a copper cable 16 mm * 4 flex, provided that it is tied from the main panel to the supply building and extended under the ground at a depth of 50 cm, and this includes the process of wickering and fixing-(unit-متر Meter)	EA	350
106	General building maintenance - <i>بالعدد : مفاقدة عامه للحمامات ويشمل العمل مفاقدة</i> <i>وتثبيت مواسير التغذية الطالعه والنازلة ومفاقدتها والمحابس واستبدال التالف ان وجد واستبدال</i> <i>الاحواض العربية او الافرنجية التالفة والحنفيات ومواسير الصرف والتغذية ويشمل البند تنظيف</i> <i>الارضيات والجدران جيدا بالماء والصابون والفلش ومع توريد وتركيب اغطية للصفايات ومفاقدة</i> <i>شبكة التغذية للمياه داخل الحمامات واستبدال المكسره منها وتثبيتها جيدا بالكليبات وتركيب حنفيات</i> <i>نيكل كروم بولاندي جديده نصف هنش ومفاقدة السيفونات مع تغيير التالفة والمكسره بنوعية انجليزي</i> <i>جديد وتركيب دش للاستحمام مع توريد وتركيب خلاط كروم مع شفاط ايطالي داخل الحمامات</i> <i>ومفاقدة المغاسل كاملة واستبدال التالف وتوريد للاماكن جديدة ان لزم الامر مع توريد مرايا امام</i> <i>المغاسل مع توريد وتركيب مشنات ارضية ان وجد تالفه و توريد وتركيب معقم جداري لليدين وبحسب</i> In number: General checking for the bathrooms, and the work includes checking and installing the rising and descending feeding pipes, the valves, replacing the damaged ones, if any, and replacing the damaged Arab or French basins, faucets, drainage and feeding pipes. It also includes cleaning the floors and walls perfectly with water, soap and Flash, in addition to supplying and installing the covers and checking water feeding network inside the bathrooms, and replacing the broken ones and fixing them well with clips, installing new Polish nickel chrome faucets, half a hench, checking siphons with replacing the damaged and broken ones with a new English quality, installing aslo a shower device, supplying and installing a chrome mixer with an Italian extractor inside the bathrooms, checking all washbasins and replacing the damaged ones and supplying new ones if necessary, with providing mirrors in front of the washbasins. In addition to supplying and installing floor washers in case of having damaged ones, and also supplying and installing a wall sanitizer for hands, according to the instructions and directions of the supervising engineer-(unit-number of toilet)	EA	8
107	General building maintenance - <i>بالمتر المربع دهان مقاوم للرطوبة والعوامل الجوية استخدام</i> <i>خارجي للذروه وبحسب المواصفات وتعليمات المهندس المشرف والتمن يشمل جميع مستلزمات</i> In square meter: The paint shall be resistant to moisture and weather conditions. External use to the peak, according to the specifications and the instructions of the supervising engineer. The price shall include all work requirements-(unit-2م Square Meter )	meter	350
108	General building maintenance - <i>كابل أبو 4 مم مفرد احمر + اسود + اصفر 2.5 مم نحاس</i> <i>فلكس على ان يتم تمديده من الطبلونات الفرعية في المبنى الى الأقسام والغرف والمكاتب لأخذ</i> mm Cable, single, red + black + yellow 2.5 mm copper flex, provided that it is extended from the sub-panels in the building to the departments, rooms and offices for the outlet (plugs) of air conditioners- (unit- حبة Piece )	EA	35
109	General building maintenance - <i>بالمتر المكعب ردم بالتربة الصالحة الخالصة من المواد</i> <i>العضوية او مستوردة من خارج الموقع داخل سور المبنى (داخل الساحة) ويلزم على طبقات لا تزيد عن</i> <i>30 سم مع الدك والرش حتى الحصول على نسبة دك لا تقل عن 90% مع مراعاة الميول المناسب</i>	meter	26

	In cubic meter, suitable soil free of organic materials or imported from outside the site shall be used to backfill within the building wall (inside the yard). Layers not exceeding 30 cm are required with tamping and spraying until getting a compaction rate of not less than 90% , taking into account the appropriate inclinations for water drainage away from the facility, and as per the instructions of the supervising engineer (unit-3م Cubic meter)		
110	General building maintenance - <i>توريد وتركيب وتشغيل مفاتيح كهرباء 3 خط يتم تركيبها في</i> Supply, installation and operation of 3 line electric switches, to be installed in rooms, offices and stores-(unit- حبة Piece )	EA	60
111	General building maintenance - <i>توريد وتركيب رفوف حديد للمخازن /مصنوعه من الحديد السميكة المقوى والمطلي بمادة عازلة وكل عمود مميز بلون مختلف/ارتفاع العمود 3.7 متر بعرض 1</i> Supply and installation of iron shelves for warehouses/Made of thick, reinforced iron, and coated with insulating material. Each column shall be distinguished in a different color/Height of the column shall be 3.7 meters, and width 1 meter, the depth shall be 80 cm, and the load shall be , with 3 floors (shelves) for each column /(unit -Iron Shelves )	EA	198
112	General building maintenance - <i>اعمال بلاط الارضيات لصالة المبنى الرئيسي بالمتر المربع - توريد وتركيب ترابيع من الجرانيت المحلي للارضيات والمداخل والصالات وبسطات السلالم من لون الأبيض والأسود مع عمل الزخارف اللازمة للصالات بالجرانيت الأحمر , البني على ان يكون متجانس اللون وخالي من العيوب وبنفس النوعية والمواصفات القديمة والتمن يشمل عمل الوزرات من نفس المادة بارتفاع (15سم) للاماكن التالية وجميع المستلزمات والمواد اللازمة حسب المواصفات ترابيع</i> Floor tiles work for the main building hall In square meter: supplying and installing tiles of local granite for floors, entrances, halls and staircases, of white and black color, with making the necessary decorations for halls with red and brown granite, provided that it shall be homogeneous in color and free from defects, with the same quality and old specifications. The price shall include making the base-boards from the same material with a height of 15cm for the damaged places, and all necessary supplies and materials according to the specifications, marble tiles (30*40*2cm) as per the instructions and directions of the supervising engineer (unit-2م Square Meter )	meter	80
113	General building maintenance - <i>بالمتر المربع توريد وتركيب بلاط سيراميك إيطالي اسباني لامع - لجدران حمامات المنفخة والتالفو والمكسرة + غرفة التدريب + وغرفة الفحص الطبي + وغرفة ادارة المعلومات نوعية ممتازة مقاس (15*20*0.5سم) وبحسب البلاط السابق المتواجد في كل غرفة ومعتمده من قبل المهندس وبحسب اللون والشكل والنوعية القديمه والتمن يشمل جميع مستلزمات العمل من مونة اسمنتية والترويب بالاسمنت الأبيض ويتم ضبط الفواصل الأفقية والراسية للبلاط السيراميك بحيث تكون متعامدة رأسيا وأفقيا بشكل خطوط مستقيمة ومتصلة رأسيا وأفقيا</i> In square meter: Supplying and installing of Italian Spanish glossy ceramic tiles for the walls of the bathrooms, replacing the damaged and broken+ training room + parasite examination room + information management room, they shall be of excellent quality, size (15 * 20 * 0.5 cm) and according to the previous tiles available in each room and as approved by the engineer, and according to color and shape of the old type. The price shall include all work requirements such as cement mortar, and grouting with white cement. The horizontal and vertical joints of the ceramic tiles shall be set so that they are perpendicular vertically and horizontally in the form of straight lines and connected vertically and horizontally-(unit-2م Square Meter )	meter	20

114	<p>مفاقدة بلاط الحمام لغرفة الحراسة من ارضيات وجددران - والغرف والممرات وتغيير المتهاالك بنفس النوعية السابقة مع التنظيف وتعبئة الفواصل باسمنت الابيض وبمواد التعقيم ومفاقدة أدوات الصرف الصحي وشبكة التغذية الموصله للحمام وشبكة الصرف الصحي من (حنفيات , شفاط , شطاف . ودش , سيفون , وجميع مايلزم ومفاقدة مغاسل اليد او تغييرها اذا احتاج الامر ونوافذ الحمام من مقابض وبيدات وريرات ومفصلات ..... الخ حسب تعليمات Sanitary works Checking bathroom tiles of the guards room including floors, walls, rooms and corridors, and changing the dilapidated ones with the same previous quality, along with cleaning and filling the joints with white cement and sterilization materials, in addition to checking the sanitation tools,feeding network connecting the bathroom and the sewage (faucets, suction, shower, siphon, and all necessary things, and also checking hand washbasins or changing them if necessary, and bathroom windows such as handles, lugs, hinges.....etc as per instructions of the supervising engineer-(unit-2م Square Meter</p>	EA	8
115	<p>بالمتر الطولي : قص احرف الرخام المخرم والمكسر للدرج - السلالم الرئيسية (المبنى الرئيسي كامل) مع الدريزنيات في صالة المبنى في الاسفل وتسوية الاحرف وتدويره بالجلخ وتعبئة الفواصل بالمونه الاسمنتية الاسمنت الأبيض مع تغيير البلاط المكسر ان وجد In مع دهان الدريزين بدهان خشبي ثلاثة اوجه خاص بالخشب حسب تعليمات المهندس المشرف linear meter: Cutting the perforated and broken marble edges for the staircase of the main stairs (the whole main building) with the balustrades in the hall of the building at the bottom, and leveling the edges and rounding them with abrasives, in addition to filling the joints with cement mortar, white cement, and changing the broken tiles, if any, and painting the railings with three-sided wooden paint special for wood, according to the instructions of the supervising engineer-(unit-م/ط Linear/meter)</p>	meter	15
116	<p>بالمتر الطولي توريد وتركيب شبك حماية للسور من الاسلاك - الشائكة بارتفاع (1.20) بحسب تعليمات المهندس المشرف In Linear meter: supplying and installing a protective net/mesh for the fence, made of barbed wire, with (1.20) in height, as per instructions of the supervising engineer (unit-م/ط Linear/meter)</p>	meter	250

## Delivery Requirements

Delivery Requirements	
<b>Delivery date and time</b>	Bidder shall deliver the goods <a href="#">Click or tap here to enter text.</a> After Contract signature.
<b>Delivery Terms (INCOTERMS 2020)</b>	<a href="#">Click or tap here to enter text.</a>
<b>Customs clearance (must be linked to INCOTERM)</b>	<input type="checkbox"/> Not applicable Shall be done by: <input type="checkbox"/> Name of organisation <input type="checkbox"/> Supplier/bidder <input type="checkbox"/> Freight Forwarder
<b>Exact Address(es) of Delivery Location(s)</b>	<a href="#">Click or tap here to enter text.</a>
<b>Distribution of shipping documents (if using freight forwarder)</b>	<a href="#">Click or tap here to enter text.</a>
<b>Packing Requirements</b>	<a href="#">Click or tap here to enter text.</a>
<b>Training on Operations and Maintenance</b>	<a href="#">Click or tap here to enter text.</a>
<b>Warranty Period</b>	<a href="#">Click or tap here to enter text.</a>
<b>After-sales service and local service support requirements</b>	<a href="#">Click or tap here to enter text.</a>
<b>Preferred Mode of Transport</b>	<a href="#">Choose an item.</a>
<b>Other information</b>	

## 6ANNEX 2: QUOTATION SUBMISSION FORM

*Bidders are requested to complete this form, including the Company Profile and Bidder's Declaration, sign it and return it as part of their quotation along with Annex 3: Technical and Financial Offer. The Bidder shall fill in this form in accordance with the instructions indicated. No alterations to its format shall be permitted and no substitutions shall be accepted.*

Name of Bidder:	Click or tap here to enter text.	
RFQ reference:	Click or tap here to enter text.	Date: Click or tap to enter a date.

### VENDOR INFORMATION SHEET<sup>1</sup>

[VENDOR INFORMATION SHEET-link.pdf](#)

### BIDDER'S DECLARATION OF CONFORMITY<sup>2</sup>

Yes	No	
<input type="checkbox"/>	<input type="checkbox"/>	On behalf of the Supplier, I hereby represent and warrant that neither the Supplier, nor any person having powers of representation, decision-making or control over it or any member of its administrative, management or supervisory body, has been the subject of a final judgement or final administrative decision for one of the following reasons: bankruptcy, insolvency or winding-up procedures; breach of obligations relating to the payment of taxes or social security contributions; grave professional misconduct, including misrepresentation, fraud; corruption; conduct related to a criminal organisation; money laundering or terrorist financing; terrorist offences or offences linked to terrorist activities; child labour and other trafficking in human beings, any discriminatory or exploitative practice, or any practice that is inconsistent with the rights set forth in the Convention on the Rights of the Child or other prohibited practices; irregularity; creating or being a shell company.
<input type="checkbox"/>	<input type="checkbox"/>	On behalf of the Supplier, I further represent and warrant that the Supplier is financially sound and duly licensed.
<input type="checkbox"/>	<input type="checkbox"/>	On behalf of the Supplier, I further represent and warrant that the Supplier has adequate human resources, equipment, competence, expertise and skills necessary to complete the contract fully and satisfactorily, within the stipulated completion period and in accordance with the relevant terms and conditions.
<input type="checkbox"/>	<input type="checkbox"/>	On behalf of the Supplier, I further represent and warrant that the Supplier complies with all applicable laws, ordinances, rules and regulations.
<input type="checkbox"/>	<input type="checkbox"/>	On behalf of the Supplier, I further represent and warrant that the Supplier will in all circumstances act in the best interests of IOM.
<input type="checkbox"/>	<input type="checkbox"/>	On behalf of the Supplier, I further represent and warrant that no official of IOM or any third party has received from, will be offered by, or will receive from the Supplier any direct or indirect benefit arising from the contract.
<input type="checkbox"/>	<input type="checkbox"/>	On behalf of the Supplier, I further represent and warrant that the Supplier has not misrepresented or concealed any material facts during the contracting process.
<input type="checkbox"/>	<input type="checkbox"/>	On behalf of the Supplier, I further represent and warrant that the Supplier will respect the legal status, privileges and immunities of IOM as an intergovernmental organization.

<sup>1</sup> [Vendor Information Sheet.xlsx](#)

<sup>2</sup> This form is mandatory to fill in and sign by every vendor who submits quotation

Yes	No	
<input type="checkbox"/>	<input type="checkbox"/>	On behalf of the Supplier, I further represent and warrant that neither the Supplier nor any persons having powers of representation, decision-making or control over the Supplier or any member of its administrative, management or supervisory body are included in the most recent Consolidated United Nations Security Council Sanctions List (the "UN Sanctions List") or are the subject of any sanctions or other temporary suspension. The Supplier will immediately disclose to IOM if it or they become subject to any sanction or temporary suspension.
<input type="checkbox"/>	<input type="checkbox"/>	On behalf of the Supplier, I further represent and warrant that the Supplier does not employ, provide resources to, support, contract or otherwise deal with any person, entity or other group associated with terrorism as per the UN Sanctions List and any other applicable anti-terrorism legislation.
<input type="checkbox"/>	<input type="checkbox"/>	On behalf of the Supplier, I further represent and warrant that, the Supplier will apply the highest ethical standards, the principles of efficiency and economy, equal opportunity, open competition and transparency, and will avoid any conflict of interest.
<input type="checkbox"/>	<input type="checkbox"/>	On behalf of the Supplier, I further represent and warrant that the Supplier undertakes to comply with the Code of Conduct, available at <a href="https://www.ungm.org/Public/CodeOfConduct">https://www.ungm.org/Public/CodeOfConduct</a> .
<input type="checkbox"/>	<input type="checkbox"/>	It is the responsibility of the Supplier to inform IOM immediately of any change to the information provided in this Declaration.
<input type="checkbox"/>	<input type="checkbox"/>	On behalf of the Supplier, I certify that I am duly authorized to sign this Declaration and on behalf of the Supplier I agree to abide by the terms of this Declaration for the duration of any contract entered into between the Supplier and IOM.
<input type="checkbox"/>	<input type="checkbox"/>	IOM reserves the right to terminate any contract between IOM and the Supplier, with immediate effect and without liability, in the event of any misrepresentation made by the Supplier in this Declaration.

Signature: \_\_\_\_\_

Name: Click or tap here to enter text.

Title: Click or tap here to enter text.

Date: Click or tap to enter a date.



### ANNEX 3: TECHNICAL AND FINANCIAL OFFER - GOODS

Bidders are requested to complete this form, sign it and return it as part of their bid along with Annex 2: Quotation Submission Form. The Bidder shall fill in this form in accordance with the instructions indicated. No alterations to its format shall be permitted and no substitutions shall be accepted.

Name of Bidder:	Click or tap here to enter text.	
RFQ reference:	4200473154	Date: Click or tap to enter a date.

#### Technical Offer

Provide the following:

- a brief description of your qualification, capacity and expertise that is relevant to the Terms of Reference.
- a brief methodology, approach and implementation plan;
- team composition and CVs of key personnel

#### Financial Offer

**Note:** Please fill out the price list form attached ([BOQs-NMCP rehabilitation of TRO warehouses .xlsx](#))

- Provide a lump sum for the provision of the services stated in the Terms of Reference of your technical offer. The lump-sum should include all costs of preparing and delivering the Services. All daily rates shall be based on an eight-hour working day.
- **Currency of Quotation: USD**

<b>Currency of the Quotation: USD</b>					
INCOTERMS: Click or tap here to enter text.					
Item No	Description	UOM	Qty	Unit price	Total price
1.	As per the price list form attached (BoQ link)				
2.	Click or tap here to enter text.				
3.	Click or tap here to enter text.				
4.	Click or tap here to enter text.				
5.	Click or tap here to enter text.				
Total Price					
Transportation Price					
Insurance Price					
Installation Price					
Training Price					
Other Charges (specify)					
<b>Total Final and All-inclusive Price</b>					

## Compliance with Requirements

	You Responses		
	Yes, we will comply	No, we cannot comply	If you cannot comply, pls. indicate counter proposal
Minimum Technical Specifications	<input type="checkbox"/>	<input type="checkbox"/>	Click or tap here to enter text.
Delivery Term (INCOTERMS)	<input type="checkbox"/>	<input type="checkbox"/>	Click or tap here to enter text.
Delivery Lead Time	<input type="checkbox"/>	<input type="checkbox"/>	Click or tap here to enter text.
Warranty and After-Sales Requirements	<input type="checkbox"/>	<input type="checkbox"/>	Click or tap here to enter text.
Validity of Quotation	<input type="checkbox"/>	<input type="checkbox"/>	Click or tap here to enter text.
Payment terms	<input type="checkbox"/>	<input type="checkbox"/>	Click or tap here to enter text.
Other requirements <i>[pls. specify]</i>	<input type="checkbox"/>	<input type="checkbox"/>	Click or tap here to enter text.

## Other Information:

Estimated weight/volume/dimension of the Consignment:	Click or tap here to enter text.
Country/ies of Origin: <i>(if export licence required this must be submitted if awarded the contract)</i>	Click or tap here to enter text.

I, the undersigned, certify that I am duly authorized to sign this quotation and bind the company below in event that the quotation is accepted.	
<b>Exact name and address of the company</b> Company Name: Click or tap here to enter text. Address: Click or tap here to enter text. Click or tap here to enter text. Phone No.: Click or tap here to enter text. Email Address: Click or tap here to enter text.	<b>Authorized Signature:</b> Date: Click or tap here to enter text. Name: Click or tap here to enter text. <b>Functional Title of Authorised Signatory:</b> Click or tap here to enter text. Email Address: Click or tap here to enter text.