Annex E Attached : Technical Sheet for Supplying Pharmaceuticals

FMF Invitation to bid for supply (Medical equipment) NO :ITB/FMF/ADE/200076/2024 المارة التكبير عطادات توريد وتوصيل أدرات ومحدات طبيةً، رقر المراكزة التكبير عطادات توريد وتوصيل أدرات ومحداث طبيةً، رقر المراكزة ا ينة عن الموسسة الطبية الميدية عن الموسسة الطبية الميدينية : الموسسة الطبية الميدينية موسسة غير ريمية بجنمية انتموية الشنفة تسعى ان تكون إلدة في العمل الإنساني و ذلك عبر خدامها الصحية و الإنقابية و الشروعية و التي تهفات إلى تحسين صحة المجتمع وبادا الخلارات مثلاً المشارعي و الخدامات المقامة ذات الجودة و المصناطية العالية . About the Field Medical Foundation:

The Field Medical Foundation is a comprehensive community-based, non-profit, developmental organization that seeks to pioneer in humanitarian action through its health, relief, and development services, which aims to improve community health and build capacity through projects and services provided with high-quality and high credibility. : تاريخ العطاء : Bid date Tender no(s): رقم العطاء 21_7 _2024 NO :ITB/FMF/ADE/200076/2024 Bid submission date : المورد. 2024 For any Information : FMF SUPPLIER Information : Company name / Treding name الاسم التجاري / اسم الشركة Contact name الاسم : Hasn Hasan Contact person الشخص الذي يمكن الاتصال به البريد /E-mail operation.dept@fmfyemen.org البريد /E-mail 02-233460 / 103 775120519 ماتف / Phone ماتف /Phone مویایل /Mobile الجمهورية اليمنية. محافظة عدن. خور مكسر. حي أكتوبر بجتب مكتب التربية والتطيم العنوان/Address Detailed Description specification Agency in Yemen Country of Origin Line item no. Examination Bed with Pillow and blanket Examination table, in 2 sections Mounted on 4 sturdy supports kygen cylinder with regulator (40L) and holder Standard Flow Rate: 40 I/min,Maximum Flow Rate Suction machine 5 Liters capacity, electric, with infant and adult tubes, Power Voltage Power 5 180 VA Pumping Rate: ≥ 20L/min Suction machine 5 Liters capacity Dual Head Stethoscope, dual head chestpiece with non-chill rubber rings, binaural, aluminium with plastic tips.
Supplied with spare diaphragm and two pair soft eartips. 5 Stethoscope 6 clinical thermometers Digital type for clinical use, measured in degree celecisus, large display, ACC. 0.1 C Digital type, good quality portable -Frequency 1.7 MHZ -Completely supplied with Aerosol hose and Mask for Adult and children, Power Supply 220 VAC ,50 Hz Nebulizer capacity max. 3 ml/min Air capacity up to 20 l/min Examination Lamp -Mobile on 5 castors LED Lamp Itensity about 15000 Lux at 50 cm -Power Supply 220- 230 V .50 Hz Mobile lamp 10 Drip stand Mobile on Castors -Double Hook -adjustable Height -material Stainless Steel

11	Steel bed ladder	_ Double Step -Steel Tubular frame Work mounted on PVC Shoes -Step fixed with Anti-Silip Rubber mat		
12	Stool,adjustable,on castors	Movable, height adjustable stool with gas spring mounted on 5 swivel castors.		
13	Guedel Airways set	TUBE, QUEDEL, airways, the set consist of 5 pcs, size No 0,1,2,3,4,5		
14	Ambu bag - Adult	resuscitation bag, ambu type, manual, adult, silicone, 1500 ml, with mask adult, oxygen reservoir bag 2600 ml.		
15	Ambu bag - Child	resuscitation bag, ambu type, manual, child, silicone, 500 ml, with mask child, oxygen reservoir bag 2500 ml		
16	Ambu bag - infant	resuscitation bag, ambu type, manual, infant, silicone, 250 ml, with mask infant, oxygen reservoir bag 600 ml		
17	Sterilizer	Fully automatic hot air steriliser with adjustable temperature from 0°C to 200°C, kills off even particularly resistant microorganisms.		

18	Hand Held Foetal Doppler	Built-in speaker. Three working modes: Real time FHR Display Mode, Averaged FHR Display Mode and Manual Mode. LCD Screen.			
19	Medical sterlizing drums	Different sizes			
20	Laboratory light microscope	Laboratory light Microscope, binocular type, with standard set, Microscope with frame Binocular tube Pair of eyepiece 10X (FN20), Quadruple revolving nosepiece,			
21	Micro Centrifuge	Micro centrifuge, tabletop, high-speed, up to 15,000 rpm with following specifications:;Bench top microcentrifuge, with speed range 500-15000rpm,			
22	Lab Water Bath	Laboratory water bath with cover (lid), 15 liker inner tank stainless steel with following features: Stabilizing temperature at 25, 37, 42 or 56°C.			
23	Pulse Oximeter	"Screen: colour LED Oxygen Saturation Measurement Range: 35-100% Heart Rate Measurement Range Auto power off Accuracy in case of weak pulse: ± 4% SpO2 Resolution: 1% SpO2, 1,1p.m. Pulse Power supply: Two 15.7 sillatine betriers AAA (not included) Graph: in bars and waves Light: the variation between the reading in darkness and in artificial light is <1% Optical sensor: Red light (660nm, 6.65mW), Infrared (880nm, 6.75mW)			
24	Trolly	"this Dressing cart should be designed to transport Dressings supplies and instruments for each surgical procedure or case to the operating room (DR) The dimensions of the surgical case cart should be approximately 9800			
25	Mobile Curtains	"Hospital Bed Side Screen, four-Fold Frame work of bed side screen constructed with ms steel tubes. Over all size of bed side screen: 244cm L x 165 cm H (opened): 60 cm L 165cm (closed) Mobile on castors Pre-treated and epoxy powder coated finishing Color Bills or Green			
26	Wheel Chairs	- Foldable - Chrome Platted Tube Frame - Seat and Backrest if reinforced Material - Fixed Armrest - Foldable Footrest - Solid Wheels Patient Stretcher - Chrome Platted Steel Tube - Removable Top covered with upholstered washable Platsit Material - Mounted on 4 Casters, no with Brakes - Complete with Side Rail, IV Stand, Oxygen Bortle Holder - Color Black *			
27	Dressing set	Dressing set contains (Kidney Dish, Gallipot, Stitch Scissors, gauze scissors, tissue scissors, Scalpel No 4, needle holder, non-toothed dissecting forceps, toothed dissecting forceps, atralght kocher artery forceps, Straight artery forceps, Curved Artery Forceps			
28	CBC MACHINE	"Hematology analyzer CBC 3 PARTS Parameters 19: WBC, LY's, MO's, GR's, LY, MO, GR, RBC, HGB, HCT, MCY, MCH, MCHC, ROWSD, RDW-CV, PLT, PCT, MPV, PDW Reagents 1 hemolyzing reagent (cyanide free), 1 diluent, 2 detegrants Sample volume 30µL for normal measurement mode or 20 µL for pro-dilution mode Throughput Approx. 60 samples /hour (Open mode) Thermal printer SUPPLY WITH UBS ONLINE*			
29	Spectrophotometer	Spectrophotometer/blochemestry analyzer, UV/Visible range 190-1000m for basic applications, Microprocessor – controlled UV/VIS spectrophotometer shall have single beam operation with automatic reference corrected measurem. The unit shall steature a hologacing ingraing monochromater with a range from 161-1000mm, (political Basimidit - Munt, Osidapsi, Kepboard controlled Modes - Absorbance, 'N Transmission of sample, Standard curve method, Coefficient method Wavelength accuracy arrange, Aurio lamp and filter selection, The spectrophotometer shall perform a self test and calibration, Power requirements 20VAC, 5009842.			
: Delivery Date الجدول الزمني لتوصيل					
Name of authorized representative of the Supplier:					
Signature and Stamp:					