



بتمويل من
الإتحاد الأوروبي



GWQ
Generations
without Qat



FURNITURE SPECIFICATIONS FOR AL-THAWRA HEALTH CENTER

NO	ITEM DESCRIPTION
1	Desktop PC
	<ul style="list-style-type: none"> • Intel Core i7-th7 • Ram 16 DDR3 • Hard 512 GB SSD • Screen 24" LCD • Intel HD Graphics 530 • Keyboard • Mouse • Windows 10 • Warranty : 1 years • Delivery period (supply within tow weeks from the date of signing the contract)
2	File cabinet, double door
	<ul style="list-style-type: none"> • Material: High-Quality Cold Rolled Steel (or better) • Shelf: 3 • Size: not less than (H1800*W900*D400mm) • High combination handle lock • Delivery period (supply within tow weeks from the date of signing the contract)
3	Printer
	<ul style="list-style-type: none"> • Printer Functions :Print, Copy, and Scan • Connectivity: USB & Wi-Fi • Print Resolution: Not less than 5,760 x 1,440 dpi • Number of Colors: 4 • Printing Speed: 33 pages per minute • Scanner Type: Contact Image Sensor (CIS) • Scan Speed (Single-sided): A4 Black - 200 dpi; 11 seconds with flatbed scan, A4 color - 200 dpi; 28 seconds with flatbed scan • Optical Resolution: 1,200 x 2,400 dpi (horizontal x vertical) • Output Tray Capacity: 30 sheets • Paper Input Capacity: 100 sheets standard • Power Supply Voltage: AC 100 V - 240 V; 50 Hz - 60 Hz • Warranty: 2-year warranty • Delivery period (supply within tow weeks from the date of signing the contract)
4	Swivel Chair
	<ul style="list-style-type: none"> • Height adjustable robust mechanism • Tilt and lock flexibility. • Durable chrome base material. • Nylon mesh back feature. • Compressed sponge seat cushion. • High efficiency • a three-year warranty • The size not less than: L*W*H (60 *58*108) CM • Chair frame, legs: Steel • Delivery period (supply within tow weeks from the date of signing the contract)



بتمويل من
الإتحاد الأوروبي



GWQ
Generations
without Qat



UN
DP

5	Steel Chairs Visitor
	<ul style="list-style-type: none">• Width 50 cm• The size not less than: 1750x570x760mm• Material: Steel• Seat: 3 seat• Delivery period (supply within tow weeks from the date of signing the contract)



بتمويل من
الإتحاد الأوروبي



GWQ
Generations
without Qat



MEDICAL EQUIPMENT'S SPECIFICATIONS AL-THAWRA HEALTH CENTER

NO	ITEM DESCRIPTION
1	CBC machine
	<ul style="list-style-type: none"> • Semi-automated system • Sample type: prediluted, whole-blood • 3part differentiation of WBC: 18 parameters + 3 histogram color; LCD display not less than 15" • Built-in thermal printer • Automatic sample probe cleaning • Memory can be stored up to 1000 samples at least including histograms. • All standard accessories to ensure a complete working system. • With a Starting kit of solutions • Suitable UPS for the analyzer • Open system • Power supply 220-240 VAC 50 Hz • Warranty: 2 years • Delivery period (supply within three weeks from the date of signing the contract)
2	ECG machine 6 channels
	<ul style="list-style-type: none"> • Automation equipment calibration • 6 electrographic standard leads measuring with simultaneous acquisition. • Visualization of at least one group of 3 leads simultaneously. • ECG patient cable with at least 5 terminals. LCD or TFT color monitor display of at least 7 inches with visualization of analogical curves, alphanumeric values measured and the related physiological limits • Equipment compatible with patients with pacemakers. • Protection against defibrillation. • Automatic internal data storing up to at least 40 ECG records. • ECG signal measurement range not smaller than -2 mV to +2 mV. • At least the following adjustable alarms: <ul style="list-style-type: none"> a) heart failure; b) ventricular fibrillation; c) tachycardia; d) bradycardia; d) electrode disconnection. • Power supply: 240 V ~ ±10%, 50/60 Hz • Rechargeable battery • Warranty 2 years • Delivery period (supply within tow weeks from the date of signing the contract)
3	Biological Microscope
	<ul style="list-style-type: none"> • Body-Single mould sturdy stand, inclined Binocular body 30° 360 rotatable head • Eyepieces-Highest quality 10 X/20mm wide angle anti-fungus field yepiece. one with pointer. Diopter adjustment MUST be present on both eyepieces. • Objectives-Parfocal, antifungus coated 4x, 10x, 40x and 100x (oil immersion) with semi planner achromatic correction. Objective should be well centred even if their position on turret is changed. • Optical system-Infinity corrected. • Stage - Double plate rackless horizontal mechanical stage preferably 100 x 140 mm with fine vernier graduations designed with convenient coaxial adjustment for slide manipulation preferably through 30 x 70 mm doubleslide holder.



بتمويل من
الإتحاد الأوروبي



GWQ
Generations
without Qat



	<ul style="list-style-type: none"> • Sub stage-Abbe condenser focusable, continuously variable iris diaphragm • Illuminator-Built-in LED light source with white light with intensity control and LED life of more than 10, 000 Hrs. • Focussing: Coaxial coarse and fine focussing knob, capable of smooth, fine focussing movement sensitivity; minimum: 300 micron; focusing stop for slide safety. • The device must be the latest and advanced model <p>Warranty</p> <ul style="list-style-type: none"> • At least 2 Years • Delivery period (supply within tow weeks from the date of signing the contract)
4	Nebulizer
	<ul style="list-style-type: none"> • Piston compressor, airflow 8 & 11t./min., max. pressure 185 kPa, bulb, • Adult & child mask, mouthpiece, nosepiece, air tube, 3 air filters • Warranty: 2 years • Delivery period (supply within tow weeks from the date of signing the contract)
5	Sphygmomanometer Mercury Stand type
	<ul style="list-style-type: none"> • Sphygmomanometer, stand type on castors , mercury column-based • Measuring scale shall be made from injected transparent polymethacrylate encases in metallic structure protected with Epoxy paint or baked-enamel • Range of measurement shall be 0 to 300mmHg as standard with at least a precision of +/-3mmHg (static measure). Display of digits shall be easily readable (4mm high minimum) • Cuff shall be made of PVC, and shall ensure a constant and precise decompression, Velcro fixation • The unit shall be recessed in a closable metallic container Supplied with: • 1 Cuff for Adult • 1 Cuff for Children • Delivery period (supply within tow weeks from the date of signing the contract)
6	Sphygmomanometer
	<ul style="list-style-type: none"> • One-hand manometer. • Delivery period (supply within tow weeks from the date of signing the contract)
7	Stethoscope, Pediatric
	<ul style="list-style-type: none"> • Stethoscope, Binaural type, Cardiac and Pulmonary examination. • Receptor shall be of dual membrane in single monobloc Stainless Steel casing. • Adult membrane shall be 45mm diameter. Children membrane shall be 36mm diameter • Ear frame shall be made of Stainless Steel and orientable as well as • Interchangeable. Nickel-steel spring • Delivery period (supply within tow weeks from the date of signing the contract)
8	Portable Ultrasound System Image With/2 Probes/ printer and UPS
	<ul style="list-style-type: none"> • To be used for Abdomen, Gynecology Obstetric, Urology) • Modes', B/B, 4B, B/M 2) • Probes: Electronic Convex Probe, Multi-Frequency (2,5 MH-5 MH) • Electronic Vignal probe Multi-Frequency (5MH-10MH) 3) Probe connector • Monitor: 12.1inch" or more • Image Adjustment: Dynamic Range B Gain, M Gain STC • Image Display: Image Direction: (L/R) (Up/Down), Shift, Cine Memory



بتمويل من
الإتحاد الأوروبي



	<ul style="list-style-type: none"> • Measurement Function: (Distance, Circumference, Area, Volume, Angle, Gestational Week Calculations, Histograms, LV Calculations, User Programmable Tables) • B/W Video printer • Trolley for the System • UPS for the System • Power Supply: 220-240 VAC, 50 Hz • tow-year warranty • Delivery period (supply within tow weeks from the date of signing the contract)
9	I.V. stand
	<ul style="list-style-type: none"> • 4 hooks, on 5 castors, adjustable from 115-210 cm, stainless steel pee • Delivery period (supply within tow weeks from the date of signing the contract)
10	Medical privacy curtains
	<ul style="list-style-type: none"> • Polyester 100% (or better) • Antibacterial: Bacteria reduction rate 99.00% • Curtain height :2.8 m • The distance from the floor to the separation curtain is usually 20-30cm • Grommet top • Steel tube • Delivery period (supply within tow weeks from the date of signing the contract)